



Maldives Civil Aviation Authority
Republic of Maldives

Maldivian Civil Aviation Regulations

MCAR-I Definitions and Abbreviations

Issue 2, Amendment 1, 16 November 2015

Foreword

Maldives Civil Aviation Authority, in exercise of the powers conferred on it under Articles 5 and 6 of the Maldives Civil Aviation Act 2/2012 has adopted this Regulation.

This Regulation shall be cited as MCAR-I Definitions and Abbreviations and shall come in to force on 16 November 2015.

This regulation contains the definitions of the terms used in other civil aviation regulations issued by the Maldives Civil Aviation Authority.

Existing definitions and abbreviations in the field of civil aviation as listed in MCAR-I Definitions and Abbreviations dated 05 June 2014 will be repealed as from 16 November 2015.



For the Civil Aviation Authority
Hussain Jaleel
Chief Executive

Table of Contents

Foreword.....	I
List of Amendments	ii
List of Effective Pages.....	iii
Table of Contents.....	iv
MCAR-1.1 GENERAL DEFINITIONS.....	1-1
MCAR-1.2 ABBREVIATIONS AND SYMBOLS.....	2-1

MCAR-I.1 General Definitions

Accelerate-stop distance available (ASDA)	The length of the take-off run available plus the length of stopway, if such stopway is declared available by the State of the aerodrome and is capable of bearing the mass of the aeroplane under the prevailing operating conditions
Acceptable means of compliance (AMC)	Non-binding standards adopted by CAA to illustrate means to establish compliance with this Regulation and its Implementing Rules
Acceptance checklist	A document used to assist in carrying out a check on the external appearance of packages of dangerous goods and their associated documents to determine that all appropriate requirements have been met with
Accepted/Acceptable	Not objected to by CAA as suitable for the purpose intended. <i>(Source: Annex III to regulation (EC) No 1899/2006 of the European parliament and of the council of 12 December 2006)</i>
Accepting unit	Air traffic control unit next to take control of an aircraft
Accident	<p>An occurrence associated with the operation of an aircraft which, in the case of a manned aircraft, takes place between the time any person boards the aircraft with the intention of flight until such time as all such persons have disembarked, or in the case of an unmanned aircraft, takes place between the time the aircraft is ready to move with the purpose of flight until such time as it comes to rest at the end of the flight and the primary propulsion system is shut down, in which:</p> <p>(a) a person is fatally or seriously injured as a result of:</p> <ol style="list-style-type: none">1. being in the aircraft, or2. direct contact with any part of the aircraft, including parts which have become detached from the aircraft, or3. direct exposure to jet blast, <p>except when the injuries are from natural causes, self-inflicted or inflicted by other persons, or when the injuries are to stowaways hiding outside the areas normally available to the passengers and crew; or</p> <p>(b) the aircraft sustains damage or structural failure which:</p> <ol style="list-style-type: none">1. adversely affects the structural strength, performance or flight characteristics of the aircraft, and2. would normally require major repair or replacement of the affected component, <p>except for engine failure or damage, when the damage is limited to a</p>

single engine, (including its cowlings or accessories), to propellers, wing tips, antennas, probes, vanes, tires, brakes, wheels, fairings, panels, landing gear doors, windscreens, the aircraft skin (such as small dents or puncture holes), or for minor damages to maintain rotor blades, tail rotor blades, landing gear, and those resulting from hail or bird strike (including holes in the radome); or

(c) the aircraft is missing or is completely inaccessible.

Note: An aircraft is considered to be missing when the official search has been terminated and the wreckage has not been located.

**Accident Investigation
Coordination Committee
(AICC)**

Appointed by the Minister for Civil Aviation and empowered to conduct an aircraft accident/incident investigation under the control of the investigator-in-charge

Acclimatised

That a crew member is considered to be acclimatised to a 2-hour wide time zone surrounding the local time of his/her point of departure. When the local time of the place where a duty commences differs by more than 2 hours from that at the place where a duty ends, the crew member is considered to be acclimatised in accordance with the values in the table below for the calculation of the maximum daily FDP.

Time difference (h) between reference time and local time where the crew member starts the subsequent duty	Time elapsed since reporting at reference time				
	<48	48-71:59	71-95:59	96-119:59	≥120
<4	B	D	D	D	D
≤6	B	X	D	D	D
≤9	B	X	X	D	D
≤12	B	X	X	X	D

‘B’ means acclimatised to the local time of the departure time zone,
 ‘D’ means acclimatised to the local time where the crew member starts his/her subsequent duty, and
 ‘X’ means that a crew member is in an unknown state of acclimatisation

Accommodation

For the purpose of standby and split duty, a quiet and comfortable place not open to the public with the ability to control light and temperature, equipped with adequate furniture that provides a crew member with a possibility to sleep, with enough capacity to accommodate all crew members present at the same time and with access to food and drink.

**Accredited medical
conclusion**

The conclusion reached by one or more medical experts acceptable CAA for the purposes of the case concerned, in consultation with flight operations or other experts as necessary.

Accredited Representative

A person designated by a State, on the basis of his or her qualifications, for the purpose of participating in an investigation conducted by another State.

Accuracy	<p>A degree of conformance between the estimated or measured value and the true value.</p> <p><i>Note: For measured positional data the accuracy is normally expressed in terms of a distance from a stated position within which there is a defined confidence of the true position falling.</i></p>
Acrobatic flight	<p>Manoeuvres intentionally performed by an aircraft involving an abrupt change in its attitude, an abnormal attitude, or an abnormal variation in speed.</p>
Adequate aerodrome	<p>An aerodrome on which the aircraft can be operated, taking account of the applicable performance requirements and runway characteristics</p>
ADS-C agreement	<p>A reporting plan which establishes the conditions of ADS-C data reporting (i.e. data required by the air traffic services unit and frequency of ADS-C reports which have to be agreed to prior to using ADS-C in the provision of air traffic services).</p> <p><i>Note: The terms of the agreement will be exchanged between the ground system and the aircraft by means of a contract, or a series of contracts.</i></p>
Advection	<p>The horizontal transfer of air mass properties by the velocity field of the atmosphere</p>
Advection fog	<p>Fog which forms in the lower part of a warm moist air mass moving over a colder surface (land or water).</p>
Adviser	<p>A person appointed by a State, on the basis of his or her qualifications, for the purpose of assisting its accredited representative in an investigation.</p>
Advisory airspace	<p>An airspace of defined dimensions, or designated route, within which air traffic advisory service is available.</p>
Advisory route	<p>A designated route along which air traffic advisory service is available.</p>
Aerial work	<p>An aircraft operation in which an aircraft is used for specialized services such as agriculture, construction, photography, surveying, observation and patrol, search and rescue, aerial advertisement, etc.</p>
Aerobatic flight	<p>An intentional manoeuvre involving an abrupt change in an aircraft's attitude, an abnormal attitude, or abnormal acceleration, not necessary for normal flight or for instruction for licences or ratings other than the aerobatic rating</p>
Aerodrome	<p>A defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft.</p>
Aerodrome climatological	<p>Concise summary of specified meteorological elements at an aerodrome,</p>

summary	based on statistical data.
Aerodrome climatological table.	Table providing statistical data on the observed occurrence of one or more meteorological elements at an aerodrome
Aerodrome control service	Air traffic control service for aerodrome traffic.
Aerodrome control tower	A unit established to provide air traffic control service to aerodrome traffic.
Aerodrome elevation.	The elevation of the highest point of the landing area.
Aerodrome mapping data (AMD).	Data collected for the purpose of compiling aerodrome mapping information. <i>Note.— Aerodrome mapping data are collected for purposes that include the improvement of the user’s situational awareness, surface navigation operations, training, charting and planning.</i>
Aerodrome mapping database (AMDB).	A collection of aerodrome mapping data organized and arranged as a structured data set.
Aerodrome meteorological office	An office designated to provide meteorological service for aerodromes serving international air navigation.
Aerodrome meteorological station	A station designated to make observations and meteorological reports for use in international air navigation.
Aerodrome operating minima	The limits of usability of an aerodrome for: (a) take-off, expressed in terms of runway visual range and/or visibility and, if necessary, cloud conditions; (b) landing in precision approach and landing operations, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H) as appropriate to the category of the operation; (c) landing in approach and landing operations with vertical guidance, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H); and (d) landing in non-precision approach and landing operations, expressed in terms of visibility and/or runway visual range, minimum descent altitude/height (MDA/H) and, if necessary, cloud conditions.
Aerodrome reference point.	The designated geographical location of an aerodrome.
Aerodrome traffic.	All traffic on the maneuvering area of an aerodrome and all aircraft flying in the vicinity of an aerodrome. <i>Note: An aircraft is in the vicinity of an aerodrome when it is in, entering or leaving an aerodrome traffic circuit.</i>
Aeronautical chart	A representation of a portion of the Earth, its culture and relief, specifically

designated to meet the requirements of air navigation. Aircraft stand. A designated area on an apron intended to be used for parking an aircraft.

Aeronautical data

A representation of aeronautical facts, concepts or instructions in a formalized manner suitable for communication, interpretation or processing.

Aeronautical fixed service (AFS).

A telecommunication service between specified fixed points provided primarily for the safety of air navigation and for the regular, efficient and economical operation of air services.

Aeronautical fixed telecommunication network (AFTN)

A worldwide system of aeronautical fixed circuits provided, as part of the aeronautical fixed service, for the exchange of messages and/or digital data between aeronautical fixed stations having the same or compatible communications characteristics.

Aeronautical Information Circular (AIC).

A notice containing information that does not qualify for the origination of a NOTAM or for inclusion in the AIP, but which relates to flight safety, air navigation, technical, administrative or legislative matters.

Aeronautical information management (AIM)

The dynamic, integrated management of aeronautical information through the provision and exchange of quality-assured digital aeronautical data in collaboration with all parties.

Aeronautical Information Publication (AIP)

A publication issued by or with the authority of a State and containing aeronautical information of a lasting character essential to air navigation.

Aeronautical information Service (AIS)

A service established within the defined area of coverage responsible for the provision of aeronautical data and aeronautical information necessary for the safety, regularity and efficiency of air navigation.

Aeronautical information.

Information resulting from the assembly, analysis and formatting of aeronautical data.

Aeronautical mobile service (RR SI.32).

A mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate; emergency position-indicating radio beacon stations may also participate in this service on designated distress and emergency frequencies.

Aeronautical station (RR SI.81).

A land station in the aeronautical mobile service. In certain instances, an aeronautical station may be located, for example, on board ship or on a platform at sea.

Aeronautical telecommunication station

A station in the aeronautical telecommunication service.

Aeroplane

A power-driven heavier-than-air aircraft, deriving its lift in flight chiefly from aerodynamic reactions on surfaces which remain fixed under given conditions of flight.

Aeroplane required to be

A type of aeroplane which is required to be operated with a co-pilot as

operated with a co-pilot	specified in the flight manual or by the air operator certificate
Aided night vision imaging system (NVIS) flight	In the case of NVIS operations, that portion of a visual flight rules (VFR) flight performed at night when a crew member is using night vision goggles (NVG)
AIP Amendment	Permanent changes to the information contained in the AIP.
AIP Supplement	Temporary changes to the information contained in the AIP which are published by means of special pages.
Aircraft	Any machine that can derive support in the atmosphere from the reactions of the air other than the reactions of the air against the earth's surface.
Air defence identification zone (ADIZ).	Special designated airspace of defined dimensions within which aircraft are required to comply with special identification and/or reporting procedures additional to those related to the provision of air traffic services (ATS).
Air ground communication	Two-way communication between aircraft and stations or locations on the surface of the earth.
Air mass.	An extensive body of the atmosphere in which physical properties, particularly temperature and humidity, exhibit only small and continuous differences in the horizontal. It may extend over an area of several million square kilometres and over a height of several kilometres
Air operator certificate (AOC)	A certificate authorizing an operator to carry out specified commercial air transport operations
Air report	A report from an aircraft in flight prepared in conformity with requirements for position, and operational and/or meteorological reporting. <i>Note: - Details of the AIREP form are given in the PANS-ATM (ICAO Doc 4444).</i>
Air taxi operation	For the purpose of flight time and duty time limitations, non-scheduled on demand commercial air transport operations with an aeroplane with a maximum operational passenger seating configuration (MOPSC) of 19 or less
Air taxiing.	Movement of a helicopter/VTOL above the surface of an aerodrome, normally in ground effect and at a ground speed normally less than 37 km/h (20 kt). Note: The actual height may vary, and some helicopters may require air-taxiing above 8 m (25 ft) AGL to reduce ground effect turbulence or provide clearance for cargo sling loads.
Air taxiway.	A defined path on the surface established for the air taxiing of helicopters.
Air temperature.	(Also termed surface temperature in meteorology). The ambient

temperature indicated by a thermometer exposed to the air but sheltered from direct solar radiation. The temperature indicated by a thermometer placed in an instrument shelter 1.5 to two meters above ground.

Air traffic advisory service A service provided within advisory airspace to ensure separation, in so far as practical, between aircraft which are operating on IFR flight plans.

Air traffic control clearance. Authorization for an aircraft to proceed under conditions specified by an air traffic control unit.

Note 1: For convenience, the term “air traffic control clearance” is frequently abbreviated to “clearance” when used in appropriate contexts.

Note 2: The abbreviated term “clearance” may be prefixed by the words “taxi”, “take-off”, “departure”, “en route”, “approach” or “landing” to indicate the particular portion of flight to which the air traffic control clearance relates.

Air traffic control service. A service provided for the purpose of:

- (a) preventing collisions:
 - 1. between aircraft, and
 - 2. on the maneuvering area between aircraft and obstructions; and
- (b) expediting and maintaining an orderly flow of air traffic.

Air traffic control unit. A generic term meaning variously, area control centre, approach control unit or aerodrome control tower.

Air traffic flow management (ATFM). A service established with the objective of contributing to a safe, orderly and expeditious flow of air traffic by ensuring that ATC capacity is utilized to the maximum extent possible and that the traffic volume is compatible with the capacities declared by the appropriate ATS authority.

Air traffic management (ATM). The dynamic, integrated management of air traffic and airspace (including air traffic services, airspace management and air traffic flow management) — safely, economically and efficiently — through the provision of facilities and seamless services in collaboration with all parties and involving airborne and ground-based functions.

Air traffic service. A generic term meaning variously, flight information service, alerting service, air traffic advisory service, air traffic control service (area control service, approach control service or aerodrome control service).

Air traffic services airspaces. Airspaces of defined dimensions alphabetically designated, within which specific types of flights may operate and for which air traffic services and rules of operation are specified.

Note: ATS airspaces are classified as Class A to G as described in MCAR 11, 2.6.

Air traffic services reporting office	<p>A unit established for the purpose of receiving reports concerning air traffic services and flight plans submitted before departure.</p> <p><i>Note: An air traffic services reporting office may be established as a separate unit or combined with an existing unit, such as another air traffic services unit, or a unit of the aeronautical information service.</i></p>
Air traffic services unit	<p>A generic term meaning variously, air traffic control unit, flight information centre or air traffic services reporting office.</p>
Air traffic.	<p>All aircraft in flight or operating on the maneuvering area of an aerodrome.</p>
Air transit route	<p>A defined path on the surface established for the air transiting of helicopters.</p>
AIRAC	<p>An acronym (aeronautical information regulation and control) signifying a system aimed at advance notification, based on common effective dates, of circumstances that necessitate significant changes in operating practices.</p>
Airborne	<p>Entirely supported by aerodynamic forces.</p> <p><i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i></p>
Airborne collision avoidance system (ACAS).	<p>An aircraft system based on secondary surveillance radar (SSR) transponder signals which operate independently of ground based equipment to provide advice to the pilot on potential conflicting aircraft that are equipped with SSR transponders.</p>
Aircraft	<p>Any machine that can derive support in the atmosphere from the reactions of the air other than the reactions of the air against the earth's surface.</p>
Aircraft — category	<p>Classification of aircraft according to specified basic characteristics, e.g. aeroplane, helicopter, glider, free balloon</p>
Aircraft — type of	<p>All aircraft of the same basic design including all modifications thereto except those modifications which result in a change in handling or flight characteristics.</p>
Aircraft avionics	<p>A term designating any electronic device — including its electrical part — for use in an aircraft, including radio, automatic flight control and instrument systems</p>
Aircraft certificated for single-pilot operation	<p>A type of aircraft which CAA has determined, during the certification process, can be operated safely with a minimum crew of one pilot</p>
Aircraft observation	<p>The evaluation of one or more meteorological elements made from an aircraft in flight.</p>
Aircraft operations manual	<p>A manual, containing normal, abnormal and emergency procedures, checklists, limitations, performance information, details of the aircraft</p>

systems and other material relevant to the operation of the aircraft

Aircraft required to be operated with a co-pilot	A type of aircraft that is required to be operated with a co-pilot, as specified in the flight manual or by the air operator certificate
Aircraft stand	A designated area on an apron intended to be used for parking an aircraft.
Aircrew	Flight crew and cabin crew
Airframe	The fuselage, booms, nacelles, cowlings, fairings, aerofoil surfaces (including rotors but excluding propellers and rotating aerofoils of engines), and landing gear of an aircraft and their accessories and controls. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Air-ground control radio station	An aeronautical telecommunication station having primary responsibility for handling communications pertaining to the operation and control of aircraft in a given area.
Airmanship	The consistent use of good judgment and well developed knowledge, skills and attitudes to accomplish flight objectives
AIRMET information.	Information issued by a meteorological watch office concerning the occurrence or expected occurrence of specified en-route weather phenomena which may affect the safety of low-level aircraft operations and which was not already included in the forecast issued for low-level flights in the flight information region concerned or sub-area thereof.
Airport duty	A pre-notified and defined period of time during which a crew member is required by the operator to be at the airport immediately available to receive an assignment for a flight, positioning or other duty
Airship	A power-driven lighter-than-air aircraft
Airway	A control area or portion thereof established in the form of a corridor.
AIS product	Aeronautical data and aeronautical information provided in the form of the elements of the Integrated Aeronautical Information Package (except NOTAM and PIB), including aeronautical charts, or in the form of suitable electronic media.
ALERFA	The code word used to designate an alert phase.
Alert phase.	A situation wherein apprehension exists as to the safety of an aircraft and its occupants.
Alerting post.	Any facility intended to serve as an intermediary between a person reporting an emergency and a rescue coordination centre or rescue subcentre.

Alerting service.	A service provided to notify appropriate organizations regarding aircraft in need of search and rescue aid, and assist such organizations as required.
Alternate Aerodrome	<p>An aerodrome to which an aircraft may proceed when it becomes either impossible or inadvisable to proceed to or to land at the aerodrome of intended landing where the necessary services and facilities are available, where aircraft performance requirements can be met and which is operational at the expected time of use. Alternate aerodromes include the following:</p> <p>Take-of alternate: An alternate aerodrome at which an aircraft can land should this become necessary shortly after take-off and it is not possible to use the aerodrome of departure.</p> <p>En-route alternate: An adequate aerodrome along the route, which may be required at the planning stage.</p> <p><i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i></p> <p>ETOPS en-route alternate: A suitable and appropriate alternate aerodrome at which an aeroplane would be able to land after experiencing an engine shut-down or other abnormal or emergency condition while en route in an ETOPS operation.</p> <p>Destination alternate: An alternate aerodrome to which an aircraft may proceed should it become either impossible or inadvisable to land at the aerodrome of intended landing.</p> <p><i>Note: - The aerodrome from which a flight departs may also be an en-route or a destination alternate aerodrome for that flight.</i></p>
Alternative means of compliance.	Those means that propose an alternative to an existing acceptable means of compliance or those that propose new means to establish compliance with civil aviation regulations for which no associated AMC have been adopted by CAA
Altimetry system error (ASE)	The difference between the altitude indicated by the altimeter display, assuming a correct altimeter barometric setting, and the pressure altitude corresponding to the undisturbed ambient pressure
Altitude	The vertical distance of a level, a point or an object considered as a point, measured from mean sea level.
Anemometer	Instrument which measures wind speed or wind speed and direction. Cup anemometer is used to measure the wind speed from the speed of rotation of a windmill which consist of 3 or 4 hemispherical or conical cups, each fixed to the ends of horizontal arms attached to a vertical axis. Byram anemometer is a variety of the cup anemometer. Counting anemometer

has cups or a fan whose rotation is transmitted to a technical counter which integrates directly the air movement speed. Hand anemometer is small portable anemometer held at arm's length by an observer making a wind speed measurement. Pressure tube anemometer (Dines anemometer) is an instrument which derives wind speed from measurements of the dynamic wind pressures. Wind blowing into a tube develops a pressure greater than the static pressure, while wind blowing across a tube develops a pressure less than the static. This pressure difference is proportional to the square of the wind speed.

Aneroid barometer

An instrument for measuring atmospheric pressure. It is constructed on the following principles: an aneroid capsule (Vidie capsule, which is a thin, disk-shaped box or capsule, usually metallic) is partially evacuated of gas, and is restrained from collapsing by an external or internal spring. The deflection of the spring will be nearly proportional to the difference between the internal and external pressures. Magnification of the spring deflection is obtained both by connecting capsules in series and by mechanical linkages.

Anticipated operating conditions

Those conditions which are known from experience or which can be reasonably envisaged to occur during the operational life of the aircraft taking into account the operations for which the aircraft is made eligible, the conditions so considered being relative to the meteorological state of the atmosphere, to the configuration of terrain, to the functioning of the aircraft, to the efficiency of personnel and to all the factors affecting safety in flight. Anticipated operating conditions do not include:

- (a) those extremes which can be effectively avoided by means of operating procedures; and
- (b) those extremes which occur so infrequently that to require the Standards to be met in such extremes would give a higher level of airworthiness than experience has shown to be necessary and practical.

Anti-icing

in the case of ground procedures, A procedure that provides protection against the formation of frost or ice and accumulation of snow on treated surfaces of the aircraft for a limited period of time (hold-over time)

Application

Manipulation and processing of data in support of user requirements (ISO 19104*).

Approach and landing operations using instrument approach procedures

Instrument approach and landing operations are classified as follows:

Non-precision approach and landing operations. An instrument approach and landing which utilizes lateral guidance but does not utilize vertical guidance

Approach and landing operations with vertical guidance. An instrument approach and landing which utilizes lateral and vertical guidance but does not meet the requirements established for precision approach and landing

operations.

Precision approach and landing operations. An instrument approach and landing using precision lateral and vertical guidance with minima as determined by the category of operation.

Note.— Lateral and vertical guidance refers to the guidance provided either by:

- (a) a ground-based navigation aid; or*
- (b) computer generated navigation data.*

Categories of precision approach and landing operations:

Category I (CAT I) operation. A precision instrument approach and landing with a decision height not lower than 60 m (200 ft) and with either a visibility not less than 800 m or a runway visual range not less than 550 m.

Category II (CAT II) operation. A precision instrument approach and landing with a decision height lower than 60 m (200 ft), but not lower than 30 m (100 ft), and a runway visual range not less than 350 m.

Category IIIA (CAT IIIA) operation. A precision instrument approach and landing with:

- (a) decision height lower than 30 m (100 ft) or no decision height; and
- (b) a runway visual range not less than 200 m.

Category IIIB (CAT IIIB) operation. A precision instrument approach and landing with:

- (a) a decision height lower than 15 m (50 ft) or no decision height; and
- (b) a runway visual range less than 200 m but not less than 50 m.

Category IIIC (CAT IIIC) operation. A precision instrument approach and landing with no decision height and no runway visual range limitations.

Note.— Where decision height (DH) and runway visual range (RVR) fall into different categories of operation, the instrument approach and landing operation would be conducted in accordance with the requirements of the most demanding category (e.g. an operation with a DH in the range of CAT IIIA but with an RVR in the range of CAT IIIB would be considered a CAT IIIB operation or an operation with a DH in the range of CAT II but with an RVR in the range of CAT I would be considered a CAT II operation).

Approach control service Air traffic control service for arriving or departing controlled flights.

Approach control unit A unit established to provide air traffic control service to controlled flights arriving at, or departing from, one or more aerodromes.

Approach procedure with vertical guidance (APV) operation	<p>an instrument approach which utilises lateral and vertical guidance, but does not meet the requirements established for precision approach and landing operations, with a decision height (DH) not lower than 250 ft and a runway visual range (RVR) of not less than 600 m</p> <p><i>(Source: European Commission Regulation (EU) No. 800/2013 dated 14 August 2013)</i></p>
Appropriate ATS authority	<p>The relevant authority designated by the State responsible for providing air traffic services in the airspace concerned.</p>
Appropriate authority	<p>(a) Regarding flight over the high seas: The relevant authority of the State of Registry.</p> <p>(b) Regarding flight other than over the high seas: The relevant authority of the State having sovereignty over the territory being overflown.</p>
Approved (by CAA)	<p>Documented (by CAA) as suitable for the purpose intended.</p> <p><i>(Source: Annex III to regulation (EC) No 1899/2006 of the European parliament and of the council of 12 December 2006)</i></p>
Approved training	<p>Training conducted under special curricula and supervision approved by CAA.</p>
Approved training organization	<p>An organization approved by CAA to conduct approved training</p>
Apron	<p>A defined area, on a land aerodrome, intended to accommodate aircraft for purposes of loading or unloading passengers, mail or cargo, fuelling, parking or maintenance.</p>
Apron management service	<p>A service provided to regulate the activities and the movement of aircraft and vehicles on an apron.</p>
Area control centre	<p>A unit established to provide air traffic control service to controlled flights in control areas under its jurisdiction.</p>
Area control service	<p>Air traffic control service for controlled flights in control areas.</p>
Area Minimum Altitude (AMA)	<p>The minimum altitude to be used under instrument meteorological conditions (IMC) that will provide a minimum obstacle clearance within a specified area, normally formed by parallels and meridians.</p>
Area navigation (RNAV)	<p>A method of navigation which permits aircraft operation on any desired flight path within the coverage of ground or space based navigation aids or within the limits of the capability of self-contained aids, or a combination of these.</p> <p><i>Note – Area navigation includes performance based navigation as well as other operations that do not meet the definition of performance-based navigation.</i></p>

Area navigation route	An ATS route established for the use of aircraft capable of employing area navigation.
Arrival routes	Routes identified in an instrument approach procedure by which aircraft may proceed from the en-route phase of flight to an initial approach fix.
Assemble	<p>A process of merging data from multiple sources into a database and establishing a baseline for subsequent processing.</p> <p><i>Note.— The assemble phase includes checking the data and ensuring that detected errors and omissions are rectified.</i></p>
Assessment	The conclusion on the medical fitness of a person based on the evaluation of the person’s medical history and/or aero-medical examinations as required in this Part and further examinations as necessary, and/or medical tests such as, but not limited to, ECG, blood pressure measurement, blood testing, X-ray
Atmosphere	The envelope of air surrounding the Earth and bound to it more or less permanently by virtue of the Earth's gravitational attraction; the system whose chemical properties, dynamic motions, and physical processes constitute the subject matter of meteorology.
Atmosphere, International Standard	<p>The atmosphere defined in ICAO Document 7488/2.</p> <p><i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i></p>
Atmospheric Pressure.	Pressure (force per unit area) exerted by the atmosphere on any surface by virtue of its weight; it is equivalent to the weight of a vertical column of air extending above a surface of unit area to the outer limit of the atmosphere.
Atmospheric radiation	Longwave (infrared) radiation emitted by or being propagated through the atmosphere.
ATS route	<p>A specified route designed for channeling the flow of traffic as necessary for the provision of air traffic services.</p> <p><i>Note 1: The term “ATS route” is used to mean variously, airway, advisory route, controlled or uncontrolled route, arrival or departure route, etc.</i></p> <p><i>Note 2: An ATS route is defined by route specifications which include an ATS route designator, the track to or from significant points (waypoints), distance between significant points, reporting requirements and, as determined by the appropriate ATS authority, the lowest safe altitude.</i></p>
ATS surveillance service	A term used to indicate a service provided directly by means of an ATS surveillance system
ATS surveillance system	A generic term meaning variously, ADS-B, PSR, SSR or any comparable

ground-based system that enables the identification of aircraft

Note — A comparable ground-based system is one that has been demonstrated, by comparative assessment or other methodology, to have a level of safety and performance equal to or better than monopoles SSR.

Augmented flight crew

A flight crew which comprises more than the minimum number required to operate the aircraft, allowing each flight crew member to leave his/her assigned post and be replaced by another appropriately qualified flight crew member for the purpose of in-flight rest

Authorised Person

A person authorised by CAA, either generally or specifically, to have access to any aircraft involved in an accident or incident.

Automatic Dependent Surveillance Broadcast (ADS-B).

A means by which aircraft, aerodrome vehicles and other objects can automatically transmit and/or receive data such as identification, position and additional data, as appropriate, in a broadcast mode via a data link.

Automatic Dependent Surveillance Contract (ADS-C).

A means by which the terms of an ADS-C agreement will be exchanged between the ground system and the aircraft, via a data link, specifying under what conditions ADS-C reports would be initiated, and what data would be contained in the reports.

Note: The abbreviated term “ADS contract” is commonly used to refer to ADS event contract, ADS demand contract, ADS periodic contract or an emergency mode.

Automatic terminal information service (ATIS)

The automatic provision of current, routine information to arriving and departing aircraft throughout 24 hours or a specified portion thereof:

Data link-automatic terminal information service (D-ATIS). The provision of ATIS via data link.

Voice-automatic terminal information service (Voice-ATIS). The provision of ATIS by means of continuous and repetitive voice broadcasts.

Auxiliary Power Unit (APU)

Any gas turbine-powered unit delivering rotating shaft power, compressor air, or both which is not intended for direct propulsion of an aircraft.

(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)

Balloon

A non-power-driven lighter-than-air aircraft

Balloon empty mass

The mass determined by weighing the balloon with all the installed equipment as specified in the AFM.

(Source: European Commission Regulation (EU) No. 379/2014 dated 24 April 2014)

Bare Earth

Surface of the Earth including bodies of water and permanent ice and snow,

and excluding vegetation and man-made objects.

Barograph

A recording barometer. Either daily or weekly barographs are used.

Barometer

An instrument for measuring atmospheric pressure. There are two types of barometers which are commonly used in meteorology: the mercury barometer and the aneroid barometer

Base turn

A turn executed by the aircraft during the initial approach between the end of the outbound track and the beginning of the intermediate or final approach track. The tracks are not reciprocal.

Note: Base turns may be designated as being made either in level flight or while descending, according to the circumstances of each individual procedure.

Basic instrument training device model (BITD model)

A defined hardware and software combination, which has obtained a BITD qualification

Break

A period of time within an FDP, shorter than a rest period, counting as duty and during which a crew member is free of all tasks

Briefing

Oral commentary on existing and/or expected meteorological conditions.

CAA

Maldives Civil Aviation Authority

Cabin crew member

A crew member who performs, in the interest of safety of passengers, duties assigned by the operator or the pilot-in-command of the aircraft, but who shall not act as a flight crew member

Calendar

Discrete temporal reference system that provides the basis for defining temporal position to a resolution of one day (ISO 19108*).

Canopy

Bare Earth supplemented by vegetation height.

Category I (CAT I) approach operation

A precision instrument approach and landing using an instrument landing system (ILS), microwave landing system (MLS), GLS (ground-based augmented global navigation satellite system (GNSS/GBAS) landing system), precision approach radar (PAR) or GNSS using a satellite-based augmentation system (SBAS) with a decision height (DH) not lower than 200 ft and with a runway visual range (RVR) not less than 550 m for aeroplanes and 500 m for helicopters

(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)

Category II (CAT II) operation

a precision instrument approach and landing operation using ILS or MLS with:

- (a) DH below 200 ft but not lower than 100 ft; and
- (b) (b) RVR of not less than 300 m.

	<p><i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i></p>
Category IIIA (CAT IIIA) operation	<p>a precision instrument approach and landing operation using ILS or MLS with:</p> <ul style="list-style-type: none">(a) (a) DH lower than 100 ft; and(b) (b) RVR not less than 200 m. <p><i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i></p>
Category IIIB (CAT IIIB) operation	<p>a precision instrument approach and landing operation using ILS or MLS with:</p> <ul style="list-style-type: none">(a) (a) DH lower than 100 ft, or no DH; and(b) (b) RVR lower than 200 m but not less than 75 m. <p><i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i></p>
Category A	<p>With respect to helicopters. A multi-engined helicopter designed with engine and system isolation features specified in the applicable airworthiness codes and capable of operations using take-off and landing data scheduled under a critical engine failure concept that assures adequate designated surface area and adequate performance capability for continued safe flight or safe rejected take-off in the event of engine failure;</p>
Category B	<p>With respect to helicopters. A single-engined or multi-engined helicopter that does not meet category A standards. Category B helicopters have no guaranteed capability to continue safe flight in the event of an engine failure, and unscheduled landing is assumed</p>
Causes	<p>Actions, omissions, events, conditions, or a combination thereof, which led to the accident or incident.</p>
Ceiling	<p>The height above the ground or water of the base of the lowest layer of cloud below 6 000 metres (20 000 feet) covering more than half the sky.</p>
Certificate	<p>Any approval, licence or other document issued as the result of certification.</p> <p><i>(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)</i></p>
Certification	<p>Any form of recognition that a product, part or appliance, organisation or person complies with the applicable requirements, as well as the issuance of the relevant certificate attesting such compliance.</p> <p><i>(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)</i></p>
Certification specifications (CS)	<p>Technical standards adopted by CAA indicating means to show compliance with civil aviation regulations and which can be used by an organisation for</p>

the purpose of certification

Certifying Staff

Personnel responsible for the release of an aircraft or a component after maintenance.

(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)

Change-over point

The point at which an aircraft navigating on an ATS route segment defined by reference to very high frequency omni directional radio ranges is expected to transfer its primary navigational reference from the facility behind the aircraft to the next facility ahead of the aircraft.

Note: Change-over points are established to provide the optimum balance in respect of signal strength and quality between facilities at all levels to be used and to ensure a common source of azimuth guidance for all aircraft operating along the same portion of a route segment.

Chicago Convention

The Convention on International Civil Aviation and its Annexes, signed in Chicago on 7 December 1944.

(Source: (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)

Circling

The visual phase of an instrument approach to bring an aircraft into position for landing on a runway/FATO that is not suitably located for a straight-in approach

Cirrocumulus (CC)

A principal high-level cloud type (cloud genus), appearing as a thin, white patch or layer of cloud without shading, composed of very small elements in the form of grains, ripples, etc., merged or separated, and more or less regularly arranged; most of the elements have an apparent width of less than one degree.

Cirrostratus (CS)

A principal high-level cloud type (cloud genus), appearing as a transparent, whitish cloud veil of fibrous (hair-like) or smooth appearance, totally or partially covering the sky, and often producing halo phenomena, either partial or complete.

Cirrus (CI)

A principal high-level cloud type (cloud genus), appearing as a detached clouds in the form of white, delicate filaments or white or mostly white patches or narrow bands. These clouds have a fibrous (hair-like) appearance, or a silky sheen, or both. Because cirrus elements are too narrow, they do not produce a complete circular halo.

Civil Aircraft

Any aircraft on the civil register of a State, other than those which that State treats as being in the service of the State, either permanently or temporarily.

Clear sky

Sky with a total cloud cover of less than one okta (or one-tenth in the United States).

Clearance limit	The point to which an aircraft is granted an air traffic control clearance.
Clearway	A defined rectangular area on the ground or water under the control of the appropriate authority, selected or prepared as a suitable area over which an aeroplane may make a portion of its initial climb to a specified height;
Clearway	A defined rectangular area on the ground or water under the control of the appropriate authority, selected or prepared as a suitable area over which an aeroplane may make a portion of its initial climb to a specified height.
Climate	Synthesis of weather conditions in a given area, characterized by long-term statistics (mean values, variances, probabilities of extreme values, etc.) of the meteorological elements in that area. Polar climate (arctic climate) is generally the climate of a geographical polar region, most commonly taken to be a climate which is too cold to support the growth of trees.
Cloud	A hydrometeor consisting of a visible aggregate of minute particles of liquid water or ice, or both, suspended in the free air and usually not touching the Earth's surface. It may also include larger particles of liquid water or ice (precipitation particles) and non-aqueous liquid or solid particles such as those present in fumes, smoke and dust (aerosols). Cloudiness is the same as cloud cover; but usually it is used in a very general sense.
Cloud amount (cover)	That portion of the sky cover which is attributed to clouds. The unit of measurement is the okta or tenths (meaning one-eighth or one-tenth) of the sky dome as seen by the observer.
Cloud base	The height of the base of the lowest observed or forecast cloud element in the vicinity of an aerodrome or operating site or within a specified area of operations, normally measured above aerodrome elevation or, in the case of offshore operations, above mean sea level
Cloud of operational significance	A cloud with the height of cloud base below 1500 m (5000 ft) or below the highest minimum sector altitude, whichever is greater, or a cumulonimbus cloud or a towering cumulus cloud at any height.
Code share	An arrangement under which an operator places its designator code on a flight operated by another operator, and sells and issues tickets for that flight
Colour safe	The ability of an applicant to readily distinguish the colours used in air navigation and correctly identify aviation coloured lights
Command and control (C2) link.	The data link between the remotely piloted aircraft and the remote pilot station for the purposes of managing the flight.
Commander	As used with respect to aircraft operations, is defined in MCAR-OPS I. <i>(Source: JAR-I)</i>

Commercial air transport (CAT) operation	An aircraft operation to transport passengers, cargo or mail for remuneration or other valuable consideration
Commercial operation	<p>Any operation of an aircraft, in return for remuneration or other valuable consideration, which is available to the public or, when not made available to the public, which is performed under a contract between an operator and a customer, where the latter has no control over the operator.</p> <p><i>(Source: (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)</i></p>
Competency	A combination of skills, knowledge and attitudes required to perform a task to the prescribed standard.
Competency element	An action that constitutes a task that has a triggering event and a terminating event that clearly defines its limits, and an observable outcome
Competency unit	A discrete function consisting of a number of competency elements
Complex motor-powered aircraft	<p>(a) an aeroplane:</p> <ul style="list-style-type: none">— with a maximum certificated take-off mass exceeding 5 700 kg, or— certificated for a maximum passenger seating configuration of more than nineteen, or— certificated for operation with a minimum crew of at least two pilots, or— equipped with (a) turbojet engine(s) or more than one turboprop engine, or <p>(b) a helicopter certificated:</p> <ul style="list-style-type: none">— for a maximum take-off mass exceeding 3 175 kg, or— for a maximum passenger seating configuration of more than nine, or— for operation with a minimum crew of at least two pilots, or <p>(c) a tilt rotor aircraft</p> <p><i>(Source: (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)</i></p>
Component	<p>Any engine, propeller, part or appliance.</p> <p><i>(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)</i></p>
Condensation	The physical process by which a vapour becomes a liquid or solid; the opposite to evaporation. In meteorological usage, this term is applied only to transformation from vapour to liquid; any process in which a solid forms directly from its vapour is termed sublimation, as is the reverse process.
Conference communications	Communication facilities whereby direct speech conversation may be conducted between three or more locations simultaneously.
Confidence level	The probability that the true value of a parameter is within a certain interval around the estimate of its value.

Note.— The interval is usually referred to as the accuracy of the estimate.

Configuration (as applied to the aeroplane).	A particular combination of the positions of the moveable elements, such as wing flaps and landing gear, etc., that affect the aerodynamic characteristics of the aeroplane
Configuration deviation list (CDL)	A list established by the organization responsible for the type design with the approval of the State of Design which identifies any external parts of an aircraft type which may be missing at the commencement of a flight, and which contains, where necessary, any information on associated operating limitations and performance correction.
Congested area	in relation to a city, town or settlement, any area which is substantially used for residential, commercial or recreational purposes
Consultation	Discussion with a meteorologist or another qualified person of existing and/or expected meteorological conditions relating to flight operations; a discussion includes answers to questions.
Contaminated runway	A runway of which more than 25 % of the runway surface area within the required length and width being used is covered by the following: (a) surface water more than 3 mm (0,125 in) deep, or by slush, or loose snow, equivalent to more than 3 mm (0,125 in) of water; (b) snow which has been compressed into a solid mass which resists further compression and will hold together or break into lumps if picked up (compacted snow); or (c) ice, including wet ice;
Contingency fuel.	The fuel required to compensate for unforeseen factors that could have an influence on the fuel consumption to the destination aerodrome
Continuing airworthiness	All the processes ensuring that, at any time in its operating life, the aircraft complies with the airworthiness requirements in force and is in a condition for safe operation. <i>(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)</i>
Continuing oversight	The tasks to be conducted to verify that the conditions under which a certificate has been granted continue to be fulfilled at any time during its period of validity, as well as the taking of any safeguard measure. <i>(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)</i>
Continuous descent final approach (CDFA)	A technique, consistent with stabilised approach procedures, for flying the final-approach segment of a non-precision instrument approach procedure as a continuous descent, without level-off, from an altitude/height at or above the final approach fix altitude/height to a point approximately 15 m (50 ft) above the landing runway threshold or the point where the flare manoeuvre shall begin for

the type of aircraft flown.

Contour line	A line on a map or chart connecting points of equal elevation.
Control area	A controlled airspace extending upwards from a specified limit above the earth.
Control zone	A controlled airspace extending upwards from the surface of the earth to a specified upper limit.
Controlled aerodrome	An aerodrome at which air traffic control service is provided to aerodrome traffic. <i>Note: The term “controlled aerodrome” indicates that air traffic control service is provided to aerodrome traffic but does not necessarily imply that a control zone exists.</i>
Controlled airspace	An airspace of defined dimensions within which air traffic control service is provided in accordance with the airspace classification. <i>Note: Controlled airspace is a generic term which covers ATS airspace Classes A, B, C, D and E as described in MCAR 11, 2.6.</i>
Controlled flight	Any flight which is subject to an air traffic control clearance.
Controller-pilot data link communications (CPDLC)	A means of communication between controller and pilot, using data link for ATC communications.
Convection	Atmospheric motions that are predominantly vertical, resulting in vertical transport and mixing of atmospheric properties; distinguished from advection
Convection cloud	Cumuliform cloud which forms in the atmosphere as a result of convection. Such clouds are also called clouds of vertical development. A cloud that has its base in the low height range but extends upward into the middle or high altitudes.
Conversion report	A report on the basis of which a licence may be converted into a Part-FCL/MCAR-66 licence
Converted meteorological visibility (CMV)	A value, equivalent to an RVR, which is derived from the reported meteorological visibility. <i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i>
Co-pilot	A pilot serving in any piloting capacity other than as pilot-in-command or commander, but excluding a pilot who is on board the aircraft for the sole purpose of receiving flight instruction for a licence or rating. <i>(Source: JAR-1)</i>

Credit	Recognition of alternative means or prior qualifications
Credit report	A report on the basis of which prior experience or qualifications may be recognised
Crew member	A person assigned by an operator to duty on an aircraft during a flight duty period.
Critical Engine	<p>The engine whose failure would most adversely affect the performance or handling qualities of an aircraft.</p> <p><i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i></p>
Critical phases of flight	<p>In the case of aeroplanes means the take-off run, the take-off flight path, the final approach, the missed approach, the landing, including the landing roll, and any other phases of flight as determined by the pilot-in-command or commander</p> <p>In the case of helicopters means taxiing, hovering, take-off, final approach, missed approach, the landing and any other phases of flight as determined by the pilot-in-command or commander</p>
Cross-country	A flight between a point of departure and a point of arrival following a pre-planned route using standard navigation procedures.
Cruise climb	An aeroplane cruising technique resulting in a net increase in altitude as the aeroplane mass decreases.
Cruise relief pilot	A flight crew member who is assigned to perform pilot tasks during cruise flight, to allow the pilot in- command or a co-pilot to obtain planned rest
Cruising level	A level maintained during a significant portion of a flight.
Culture	All man-made features constructed on the surface of the Earth, such as cities, railways and canals.
Cumulonimbus (CB)	A principal cloud type (cloud genus) of vertical development. Exceptionally dense and vertically developed clouds, occurring either as isolated clouds or as a line or wall of clouds with separated upper portions. These clouds appear as mountains or huge towers, at least a part of the upper portions of which are usually smooth, fibrous, or striated, and almost flattened. This part often spreads out in the form of anvil (incus) or vast plume. Under the base of cumulonimbus, which is very dark, there frequently exists virga, precipitation, and low, ragged clouds, either merged with it or not. Its precipitation is often heavy and always of a showery nature.
Cumulus	A principal low-level cloud type (cloud genus) in the form of individual, detached elements which are generally dense and possess sharp non-fibrous outlines. These elements develop vertically, appearing as rising mounds, domes, or towers, the upper parts of which often resembles a cauliflower.

The sunlit parts of these clouds are mostly brilliant white; their bases are relatively dark and nearly horizontal. Near the horizon the vertical development of cumulus often causes the individual clouds to appear merged. If precipitation occurs, it is usually of a showery nature.

Current flight plan	The flight plan, including changes, if any, brought about by subsequent clearances.
Cyclic redundancy check (CRC)	A mathematical algorithm applied to the digital expression of data that provides a level of assurance against loss or alteration of data.
Cyclone (Depression, low, low pressure area)	Area in the atmosphere, wherein the pressures are lower than those of the surrounding region at the same level. It is represented on a synoptic chart by a system of isobars at a specified altitude level (or a system of contours at a specified pressure level) which enclose relatively low values of pressure (or altitude). In its development a cyclone usually has the following phases. A wave (young) cyclone forms and moves along a front. Mature cyclone has well-developed warm sectors and both cold and warm fronts. Occluded cyclone is that within which there has developed an occluded front.
Cyclonic circulation	Atmospheric circulation associated with a cyclone (depression, low pressure area). It is counter clockwise in the Northern Hemisphere and clockwise in the Southern Hemisphere.
Damp lease	A lease arrangement whereby a lessor provides an aircraft with partial crew to the lessee. <i>(Source: Singapore CAA Advisory Circular AC AOC-8(2))</i>
Damp runway	A runway where the surface is not dry, but when the moisture on it does not give it a shiny appearance;
Danger area.	An airspace of defined dimensions within which activities dangerous to the flight of aircraft may exist at specified times.
Dangerous goods	Articles or substances which are capable of posing a risk to health, safety, property or the environment and which are shown in the list of dangerous goods in the Technical Instructions or which are classified according to those Instructions <i>Note — Dangerous goods are classified in ICAO Annex 18, Chapter 3</i>
Dangerous goods accident	An occurrence associated with and related to the transport of dangerous goods by air which results in fatal or serious injury to a person or major property damage
Dangerous goods incident	(a) an occurrence other than a dangerous goods accident associated with and related to the transport of dangerous goods by air, not necessarily occurring on board an aircraft, which results in injury to a person, property damage, fire, breakage, spillage, leakage of fluid or radiation or other evidence that the

- integrity of the packaging has not been maintained
- (b) any occurrence relating to the transport of dangerous goods which seriously jeopardises an aircraft or its occupants

Data link communications A form of communication intended for the exchange of messages via a data link.

Data link-automatic terminal information service (D-ATIS) The provision of ATIS via data link.

Data product Data set or data set series that conforms to a data product specification (ISO 19131*).

Data product specification Detailed description of a data set or data set series together with additional information that will enable it to be created, supplied to and used by another party (ISO 19131).

Note:- A data product specification provides a description of the universe of discourse and a specification for mapping the universe of discourse to a data set. It may be used for production, sales, end-use or other purpose.

Data quality A degree or level of confidence that the data provided meets the requirements of the data user in terms of accuracy, resolution and integrity.

Data set Identical collection of data (ISO 19101).

Data set series Collection of data sets sharing the same product specification (ISO 19115*).

Datum Any quantity or set of quantities that may serve as a reference or basis for the calculation of other quantities (ISO 19104*).

Decision altitude (DA) or decision height (DH) A specified altitude or height in the precision approach or approach with vertical guidance at which a missed approach must be initiated if the required visual reference to continue the approach has not been established.

Note 1 — Decision altitude (DA) is referenced to mean sea level and decision height (DH) is referenced to the threshold elevation.

Note 2 — The required visual reference means that section of the visual aids or of the approach area which should have been in view for sufficient time for the pilot to have made an assessment of the aircraft position and rate of change of position, in relation to the desired flight path. In Category III operations with a decision height the required visual reference is that specified for the particular procedure and operation.

Note 3 — For convenience where both expressions are used they may be

written in the form “decision altitude/ height” and abbreviated “DA/H”.

Declared capacity	A measure of the ability of the ATC system or any of its subsystems or operating positions to provide service to aircraft during normal activities. It is expressed as the number of aircraft entering a specified portion of airspace in a given period of time, taking due account of weather, ATC unit configuration, staff and equipment available, and any other factors that may affect the workload of the controller responsible for the airspace.
Defined point after take-off (DPATO)	The point, within the take-off and initial climb phase, before which the helicopter’s ability to continue the flight safely, with the critical engine inoperative, is not assured and a forced landing may be required
Defined point before landing (DPBL)	The point within the approach and landing phase, after which the helicopter’s ability to continue the flight safely, with the critical engine inoperative, is not assured and a forced landing may be required
De-icing	in the case of ground procedures. A procedure by which frost, ice, snow or slush is removed from an aircraft in order to provide uncontaminated surfaces
Delayed reporting	The postponement of a scheduled FDP by the operator before a crew member has left his/her place of rest
Depression	The same as cyclone.
Design landing mass	The maximum mass of the aircraft at which, for structural design purposes, it is assumed that it will be planned to land.
Design take-off mass	The maximum mass at which the aircraft, for structural design purposes, is assumed to be planned to be at the start of the take-off run
Design taxiing mass	The maximum mass of the aircraft at which structural provision is made for load liable to occur during use of the aircraft on the ground prior to the start of take-off
Detect and avoid	The capability to see, sense or detect conflicting traffic or other hazards and take the appropriate action.
DETRESFA	The code word used to designate a distress phase.
Dew point (Dew-point temperature)	The temperature to which a given parcel of air must be cooled at constant pressure and constant water-vapour content in order for saturation to occur. When this temperature is below 0 °C, it is called the frost point.
Digital Elevation Model (DEM)	The representation of terrain surface by continuous elevation values at all intersections of a defined grid, referenced to common datum.

Note.— Digital Terrain Model (DTM) is sometimes referred to as DEM.

Direct transit arrangements	Special arrangements approved by the public authorities concerned by which traffic which is pausing briefly in its passage through the Contracting State may remain under their direct control.
Discrete source damage	Structural damage of the aeroplane that is likely to result from: impact with a bird, uncontained fan blade failure, uncontained engine failure, uncontained high-energy rotating machinery failure or similar causes.
Displaced Threshold	A threshold not located at the extremity of a runway
Disruptive schedule	<p>A crew member's roster comprising an FDP or a combination of FDPs starting, finishing during or encroaching any portion of the day or of the night where a crew member is acclimatised which disrupts the sleep opportunity during the optimal sleep time window. A schedule may be disruptive due to early starts, late finishes and night duties.</p> <p>(a) 'Early type' of disruptive schedule means:</p> <ol style="list-style-type: none">1. for 'early start' a duty period starting in the period between 05:00 and 05:59 in the time zone to which a crew member is acclimatised; and2. for 'late finish' a duty period finishing in the period between 23:00 and 01:59 in the time zone to which a crew member is acclimatised. <p>(b) 'Late type' of disruptive schedule means:</p> <ol style="list-style-type: none">1. for 'early start' a duty period starting in the period between 05:00 and 06:59 in the time zone to which a crew member is acclimatised; and2. for 'late finish' a duty period finishing in the period between 00:00 and 01:59 in the time zone to which a crew member is acclimatised. <p>(c) 'Night duty' means a duty period encroaching any portion of the period between 02:00 and 04:59 in the time zone to which the crew is acclimatised</p>
Distance DR	The horizontal distance that the helicopter has travelled from the end of the take-off distance available
Distress phase	A situation wherein there is reasonable certainty that an aircraft and its occupants are threatened by grave and imminent danger or require immediate assistance.
Ditching	The forced landing of an aircraft on water.
Downstream clearance	A clearance issued to an aircraft by an air traffic control unit that is not the current controlling authority of that aircraft.
Dry lease agreement	An agreement between undertakings pursuant to which the aircraft is operated under the air operator certificate (AOC) of the lessee

Dry operating mass	The total mass of the aircraft ready for a specific type of operation, excluding usable fuel and traffic load
Dry runway	A runway which is neither wet nor contaminated, and includes those paved runways which have been specially prepared with grooves or porous pavement and maintained to retain 'effectively dry' braking action even when moisture is present
Dual instruction time	Flight time during which a person is receiving flight instruction from a properly authorized pilot on board the aircraft
Duty	Any task that a crew member performs for the operator, including flight duty, administrative work, giving or receiving training and checking, positioning, and some elements of standby
Duty period	A period which starts when a crew member is required by an operator to report for or to commence a duty and ends when that person is free of all duties
Eastward-Westward and Westward-Eastward transition	The transition at home base between a rotation crossing 6 or more time zones in one direction and a rotation crossing 4 or more time zones in the opposite direction
ELAI aircraft	<p>means the following manned European Light Aircraft:</p> <ul style="list-style-type: none">(a) an aeroplane with a maximum take-off mass (MTOM) of 1200-kg or less that is not classified as complex motor-powered aircraft;(b) a sailplane or powered sailplane of 1200 kg MTOM or less;(c) a balloon with a maximum design lifting gas or hot air volume of not more than 3400 m³ for hot air balloons, 1050 m³ for gas balloons, 300 m³ for tethered gas balloons;(d) an airship designed for not more than four occupants and a maximum design lifting gas or hot air volume of not more than 3400 m³ for hot air airships and 1000 m³ for gas airships. <p><i>(Source: European Commission Regulation (EU) No 1321/2014 of 26 November 2014)</i></p>
ELA2 aircraft	<p>means the following manned European Light Aircraft</p> <ul style="list-style-type: none">(a) an aeroplane with a Maximum Take-off Mass (MTOM) of 2000 kg or less that is not classified as complex motor-powered aircraft;(b) a sailplane or powered sailplane of 2 000 kg MTOM or less;(c) a balloon;(d) (d) a Very Light Rotorcraft with a MTOM not exceeding 600 kg which is of a simple design, designed to carry not more than two occupants, not powered by turbine and/or rocket engines; restricted to VFR day operations <p><i>(Source: European Commission Regulation (EU) No. 800/2013 dated 14 August 2013)</i></p>

Electronic Aeronautical Chart Display	An electronic device by which flight crews are enabled to execute, in a convenient and timely manner, route planning, route monitoring and navigation by displaying required information.
Elevated final approach and take-off area (elevated FATO)	A FATO that is at least 3 m above the surrounding surface;
Elevation	The vertical distance of a point or a level, on or affixed to the surface of the earth, measured from mean sea level.
Ellipsoid Height (GEODETTIC HEIGHT)	The height related to the reference ellipsoid, measured along the ellipsoidal outer normal through the point in question.
Emergency locator transmitter (ELT)	<p>A generic term describing equipment which broadcast distinctive signals on designated frequencies and, depending on application, may be automatically activated by impact or be manually activated. An ELT may be any of the following:</p> <p>Automatic fixed ELT (ELT(AF)). An automatically activated ELT which is permanently attached to an aircraft.</p> <p>Automatic portable ELT (ELT(AP)). An automatically activated ELT which is rigidly attached to an aircraft but readily removable from the aircraft.</p> <p>Automatic deployable ELT (ELT(AD)). An ELT which is rigidly attached to an aircraft and which is automatically deployed and activated by impact, and, in some cases, also by hydrostatic sensors. Manual deployment is also provided.</p> <p>Survival ELT (ELT(S)). An ELT which is removable from an aircraft, stowed so as to facilitate its ready use in an emergency, and manually activated by survivors.</p>
Emergency phase	A generic term meaning, as the case may be, uncertainty phase, alert phase or distress phase.
En-route alternate (ERA) aerodrome	<p>An adequate aerodrome along the route, which may be required at the planning stage.</p> <p><i>(Source: European Commission Regulation (EU) No. 965/2012 dated 25 October 2012)</i></p>
Engine	A unit used or intended to be used for aircraft propulsion. It consists of at least those components and equipment necessary for functioning and control, but excludes the propeller (if applicable).
Enhanced vision system (EVS)	A system to display electronic real-time images of the external scene achieved through the use of imaging sensors

Error	<p>An action or inaction by an operational person that leads to deviations from organizational or the operational person's intentions or expectations.</p> <p><i>Note — See Attachment E of ICAO Annex 13 — Aircraft Accident and Incident Investigation for a description of operational personnel.</i></p>
Error management	<p>The process of detecting and responding to errors with countermeasures that reduce or eliminate the consequences of errors and mitigate the probability of further errors or undesired states.</p> <p><i>Note — See Attachment C to Chapter 3 of the ICAO Procedures for Air Navigation Services — Training (PANS-TRG, Doc 9868) and Circular 314 — Threat and Error Management (TEM) in Air Traffic Control for a description of undesired states.</i></p>
Estimated off-block time.	<p>The estimated time at which the aircraft will commence movement associated with departure.</p>
Estimated time of arrival	<p>For IFR flights, the time at which it is estimated that the aircraft will arrive over that designated point, defined by reference to navigation aids, from which it is intended that an instrument approach procedure will be commenced, or, if no navigation aid is associated with the aerodrome, the time at which the aircraft will arrive over the aerodrome.</p> <p>For VFR flights, the time at which it is estimated that the aircraft will arrive over the aerodrome.</p>
Examination	<p>An inspection, palpation, percussion, auscultation or other means of investigation especially for diagnosing disease</p>
Expected approach time	<p>The time at which ATC expects that an arriving aircraft, following a delay, will leave the holding fix to complete its approach for a landing.</p> <p><i>Note – The actual time of leaving the holding fix will depend upon the approach clearance.</i></p>
Extended range operation	<p>Any flight by an aeroplane with two turbine power-units where the flight time at the one power unit inoperative cruise speed (in ISA and still air conditions), from a point on the route to an adequate alternate aerodrome, is greater than the threshold time approved by the State of the Operator.</p>
Eye specialist	<p>An ophthalmologist or a vision care specialist qualified in optometry and trained to recognise pathological conditions,</p>
Factor of safety	<p>A design factor used to provide for the possibility of loads greater than those assumed, and for uncertainties in design and fabrication.</p>
Fatal Injury	<p>means any injury which results in death within 30 days of the accident.</p>

Feature	Abstraction of real world phenomena (ISO 19101).
Feature attribute	Characteristic of a feature (ISO 19101). <i>Note:- A feature attribute has a name, a data type and a value domain associated with it.</i>
Feature operation	Operation that every instance of a feature type may perform (ISO 19110*). <i>Note.— An operation upon the feature type dam is to raise the dam. The result of this operation is to raise the level of water in the reservoir.</i>
Feature relationship	Relationship that links instances of one feature type with instances of the same or a different feature type (ISO 19101*).
Feature type	Class of real world phenomena with common properties (ISO 19110*). <i>Note.— In a feature catalogue, the basic level of classification is the feature type.</i>
Filed flight plan.	The flight plan as filed with an ATS unit by the pilot or a designated representative, without any subsequent changes.
Final approach	That part of an instrument approach procedure which commences at the specified final approach fix or point, or where such a fix or point is not specified, (a) at the end of the last procedure turn, base turn or inbound turn of a racetrack procedure, if specified; or (b) at the point of interception of the last track specified in the approach procedure; and ends at a point in the vicinity of an aerodrome from which: 1. a landing can be made; or 2. a missed approach procedure is initiated.
Final Approach and Take-off Area (FATO)	A defined area over which the final phase of the approach manoeuvre to hover or landing is completed and from which the take-off manoeuvre is commenced. Where the FATO is to be used by performance Class I helicopters, the defined area includes the rejected take-off area available.
Final Approach Fix or Point	That fix or point of an instrument approach procedure where the final approach segment commences.
Final approach segment	That segment of an instrument approach procedure in which alignment and descent for landing are accomplished.
Fire resistant	The capability to withstand the application of heat by a flame for a period of 5 minutes.

Note — The characteristics of an acceptable flame can be found in ISO 2685.

Fireproof

The capability to withstand the application of heat by a flame for a period of 15 minutes.

Note — The characteristics of an acceptable flame can be found in ISO 2685.

Fireproof material

A material capable of withstanding heat as well as or better than steel when the dimensions in both cases are appropriate for the specific purpose

First aid oxygen

The additional oxygen provided for the use of passengers, who do not satisfactorily recover following subjection to excessive cabin altitudes, during which they had been provided with supplemental oxygen.

(Source: JAR-I)

Flammable

With respect to a fluid or gas, means susceptible to igniting readily or exploding.

(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)

Flight and Navigation Procedures Trainer' (FNPT)

A training device which represents the flight deck or cockpit environment, including the assemblage of equipment and computer programmes necessary to represent an aircraft type or class in flight operations to the extent that the systems appear to function as in an aircraft

Flight crew member

A pilot, flight engineer, or flight navigator assigned to duty in an aircraft during flight time.

(Source: JAR-I)

Flight data analysis

A process of analysing recorded flight data in order to improve the safety of flight operations.

Flight data monitoring (FDM)

The proactive and non-punitive use of digital flight data from routine operations to improve aviation safety

Flight documentation.

Written or printed documents, including charts or forms, containing meteorological information for a flight.

Flight duty period (FDP)

A period that commences when a crew member is required to report for duty, which may include a flight or a series of flights, and finishes when the aircraft finally comes to rest and the engines are shut down, at the end of the last flight on which he/she acts as an operating crew member

Flight Information Centre

A unit established to provide flight information service and alerting service.

Flight Information Region	An airspace of defined dimensions within which flight information service and alerting service are provided.
Flight Information Service	A service provided for the purpose of giving advice and information useful for the safe and efficient conduct of flights.
Flight instructor (FI)	An instructor with the privileges to provide training in an aircraft, in accordance with Part-FCL
Flight level	<p>A surface of constant atmospheric pressure which is related to a specific pressure datum, 1013.2 hectopascals (hPa), and is separated from other such surfaces by specific pressure intervals.</p> <p><i>Note 1: A pressure type altimeter calibrated in accordance with the Standard Atmosphere:</i></p> <p><i>(a) when set to a QNH altimeter setting, will indicate altitude;</i> <i>(b) when set to a QFE altimeter setting, will indicate height above the QFE reference datum;</i> <i>(c) when set to a pressure of 1 013.2 hPa, may be used to indicate flight levels.</i></p> <p><i>Note 2: The terms “height” and “altitude”, used in Note 1 above, indicate altimetric rather than geometric heights and altitudes.</i></p>
Flight Manual	A manual, associated with the certificate of airworthiness, containing limitations within which the aircraft is to be considered airworthy, and instructions and information necessary to the flight crew members for the safe operation of the aircraft.
Flight operations officer/flight dispatcher	A person designated by the operator to engage in the control and supervision of flight operations, whether licensed or not, suitably qualified in accordance with the applicable requirements, who supports, briefs and/or assists the pilot-in-command in the safe conduct of the flight
Flight plan	Specified information provided to air traffic services units, relative to an intended flight or portion of a flight of an aircraft.
Flight procedures trainer	See flight simulation training device.
Flight recorder	Any type of recorder installed in the aircraft for the purpose of complementing accident/incident investigation.
Flight safety documents system.	A set of interrelated documentation established by the operator, compiling and organizing information necessary for flight and ground operations, and comprising, as a minimum, the operations manual and the operator’s continuing airworthiness management exposition.
Flight simulation training device (FSTD).	A training device which is:

- (a) in the case of aeroplanes, a full flight simulator (FFS), a flight training device (FTD), a flight and navigation procedures trainer (FNPT), or a basic instrument training device (BITD);
- (b) in the case of helicopters, a full flight simulator (FFS), a flight training device (FTD) or a flight and navigation procedures trainer (FNPT)

(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)

Flight simulator

See flight simulation training device.

Flight time

for aeroplanes, touring motor gliders and powered-lift, it means the total time from the moment an aircraft first moves for the purpose of taking off until the moment it finally comes to rest at the end of the flight;

for helicopters, it means the total time from the moment a helicopter's rotor blades start turning until the moment the helicopter finally comes to rest at the end of the flight, and the rotor blades are stopped;

for airships, it means the total time from the moment an airship is released from the mast for the purpose of taking off until the moment the airship finally comes to rest at the end of the flight, and is secured on the mast;

for sailplanes, it means the total time from the moment the sailplane commences the ground run in the process of taking off until the moment the sailplane finally comes to a rest at the end of flight;

for balloons, it means the total time from the moment the basket leaves the ground for the purpose of taking off until the moment it finally comes to a rest at the end of the flight.

Flight time — aeroplanes

The total time from the moment an aeroplane first moves for the purpose of taking off until the moment it finally comes to rest at the end of the flight.

Note. — Flight time as here defined is synonymous with the term “block to block” time or “chock to chock” time in general usage which is measured from the time an aeroplane first moves for the purpose of taking off until it finally stops at the end of the flight.

Flight time — helicopters

The total time from the moment a helicopter's rotor blades start turning until the moment the helicopter finally comes to rest at the end of the flight, and the rotor blades are stopped.

Flight time under Instrument Flight Rules (IFR)

All flight time during which the aircraft is being operated under the Instrument Flight Rules.

Flight Training Device (FTD)	A full size replica of a specific aircraft type's instruments, equipment, panels and controls in an open flight deck area or an enclosed aircraft flight deck, including the assemblage of equipment and computer software programmes necessary to represent the aircraft in ground and flight conditions to the extent of the systems installed in the device. It does not require a force cueing motion or visual system, except in the case of helicopter FTD levels 2 and 3, where visual systems are required.
Flight visibility	The visibility forward from the cockpit of an aircraft in flight.
Fog	A hydrometeor consisting of a visible aggregate of minute water droplets (or ice crystals), suspended in the atmosphere near the Earth's surface. According to international definition, fog reduces visibility below one kilometer. Fog differs from cloud only in that the base of fog is at the Earth's surface while clouds are above the surface. When composed of ice crystals, it is termed ice fog.
Forecast	A statement of expected meteorological conditions for a specified time or period, and for a specified area or portion of airspace.
Front	In meteorology, generally, the interface or transition zone between two air masses of different density. Since the temperature distribution is the most important regulator of the atmosphere density, a front almost invariably separates air masses of different temperature. When warmer air replaces the colder, it is a warm front, and a front is a cold one when the opposite occurs.
Frost	The condition which exists when the temperature near the Earth's surface and Earth-bound objects falls below freezing (0 °C or 32 °F).
Frost point	The highest temperature at which atmospheric moisture will sublimate in the form of hoarfrost on a cooled surface. It is analogous to the dew point.
FSTD qualification	The level of technical ability of an FSTD as defined in the compliance document
FSTD user	The organisation or person requesting training, checking or testing through the use of an FSTD to an ATO
Fuel ERA aerodrome	An ERA aerodrome selected for the purpose of reducing contingency fuel
Full Flight Simulator (FFS)	A full size replica of a specific type or make, model and series aircraft flight deck, including the assemblage of all equipment and computer programmes necessary to represent the aircraft in ground and flight operations, a visual system providing an out-of-the-flight deck view, and a force cueing motion system
GAMET area forecast	An area forecast in abbreviated plain language for low-level flights for a flight information region or sub-area thereof, prepared by the

meteorological office designated by the MMS and exchanged with meteorological offices in adjacent flight information regions, as agreed between the meteorological authorities concerned.

GBAS landing system (GLS)

An approach landing system using ground based augmented global navigation satellite system (GNSS/GBAS) information to provide guidance to the aircraft based on its lateral and vertical GNSS position. It uses geometric altitude reference for its final approach slope

General aviation operation

An aircraft operation other than a commercial air transport operation or an aerial work operation.

General circulation

(global circulation, planetary circulation) of the atmosphere. Complete statistical description of atmospheric motions over the Earth.

Geodesic distance

The shortest distance between any two points on a mathematically defined ellipsoidal surface.

Geodetic datum

A minimum set of parameters required to define location and orientation of the local reference system with respect to the global reference system/frame.

Geoid

The equipotential surface in the gravity field of the Earth which coincides with the undisturbed mean sea level (MSL) extended continuously through the continents.

Note:- The geoid is irregular in shape because of local gravitational disturbances (wind tides, salinity, current, etc.) and the direction of gravity is perpendicular to the geoid at every point.

Geoid undulation

The distance of the geoid above (positive) or below (negative) the mathematical reference ellipsoid.

Note:- In respect to the World Geodetic System — 1984 (WGS-84) defined ellipsoid, the difference between the WGS-84 ellipsoidal height and orthometric height represents WGS-84 geoid undulation.

Glide path

A descent profile determined for vertical guidance during a final approach.

Glider

A non-power-driven heavier-than-air aircraft, deriving its lift in flight chiefly from aerodynamic reactions on surfaces which remain fixed under given conditions of flight

Glider flight time

The total time occupied in flight, whether being towed or not, from the moment the glider first moves for the purpose of taking off until the moment it comes to rest at the end of the flight.

Gregorian calendar

Calendar in general use; first introduced in 1582 to define a year that more closely approximates the tropical year than the Julian calendar (ISO

19108*).

Note – In the Gregorian calendar, common years have 365 days and leap years 366 days divided into twelve sequential months.

Gregorian calendar Calendar in general use; first introduced in 1582 to define a year that more closely approximates the tropical year than the Julian calendar (ISO 19108).

Note:- In the Gregorian calendar, common years have 365 days and leap years 366 days divided into twelve sequential months.

Grid point data in digital form Computer processed meteorological data for a set of regularly spaced points on a chart, for transmission from a meteorological computer to computer in a code form suitable for automated use.

Note:- In most cases, such data are transmitted on medium- or high-speed telecommunications channels.

Ground emergency service personnel Any ground emergency service personnel (such as policemen, firemen, etc.) involved with helicopter emergency medical services (HEMSs) and whose tasks are to any extent pertinent to helicopter operations

Ground handling Services necessary for an aircraft's arrival at, and departure from, an airport, other than air traffic services.

Ground visibility The visibility at an aerodrome as reported by an accredited observer or by automatic systems.

Grounding The formal prohibition of an aircraft to take-off and the taking of such steps as are necessary to detain it

Group of balloons A categorisation of balloons, taking into account the size or capacity of the envelope

Guidance Material (GM) Non-binding material developed by the CAA that helps to illustrate the meaning of a requirement or specification and is used to support the interpretation of civil aviation regulations and AMC

Gyroplane A heavier-than-air aircraft supported in flight by the reactions of the air on one or more rotors which rotate freely on substantially vertical axes

Harness The equipment, consisting of two shoulder straps and a lap belt, which is provided to restrain a member of the flight crew against inertia loads occurring in emergency conditions.

(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)

Haze Fine dust or salt particles dispersed through a portion of the atmosphere; a

type of lithometeor. The particles are so small that they cannot be felt or individually seen with the naked eye, but they diminish horizontal visibility and give the atmosphere a characteristic opalescent appearance that subdues all colours.

Heading	The direction in which the longitudinal axis of an aircraft is pointed, usually expressed in degrees from North (true, magnetic, compass or grid).
Head-up display (HUD)	A display system which presents flight information to the pilot's forward external field of view and which does not significantly restrict the external view
Head-up guidance landing system (HUDLS)	The total airborne system that provides head-up guidance to the pilot during the approach and landing and/or missed approach procedure. It includes all sensors, computers, power supplies, indications and controls
Heavier-than-air aircraft	Any aircraft deriving its lift in flight chiefly from aerodynamic forces.
Height	The vertical distance of a level, a point or an object considered as a point, measured from a specified datum.
Helicopter	A heavier-than-air aircraft supported in flight chiefly by the reactions of the air on one or more power driven rotors on substantially vertical axes.
Helicopter hoist operation (HHO) crew member	A technical crew member who performs assigned duties relating to the operation of a hoist
Helicopter stand	An aircraft stand which provides for parking a helicopter and, where air taxiing operations are contemplated, the helicopter touchdown and liftoff.
Helideck	A FATO located on a floating or fixed offshore structure;
Heliport	An aerodrome or a defined area on a structure intended to be used wholly or in part for the arrival, departure and surface movement of helicopters.
HEMS crew member	A technical crew member who is assigned to a HEMS flight for the purpose of attending to any person in need of medical assistance carried in the helicopter and assisting the pilot during the mission
HEMS flight	A flight by a helicopter operating under a HEMS approval, the purpose of which is to facilitate emergency medical assistance, where immediate and rapid transportation is essential, by carrying: (a) medical personnel; (b) medical supplies (equipment, blood, organs, drugs); or (c) ill or injured persons and other persons directly involved.
HEMS operating base	An aerodrome at which the HEMS crew members and the HEMS helicopter may be on stand-by for HEMS operations

HEMS operating site	A site selected by the commander during a HEMS flight for helicopter hoist operations, landing and take-off.
HHO flight	A flight by a helicopter operating under an HHO approval, the purpose of which is to facilitate the transfer of persons and/or cargo by means of a helicopter hoist
HHO offshore	A flight by a helicopter operating under an HHO approval, the purpose of which is to facilitate the transfer of persons and/or cargo by means of a helicopter hoist from or to a vessel or structure in a sea area or to the sea itself
HHO passenger	A person who is to be transferred by means of a helicopter hoist
HHO site	A specified area at which a helicopter performs a hoist transfer
High-level clouds	Cirrus, Cirrocumulus and Cirrostratus are high-level clouds.
Holding procedure	A predetermined manoeuvre which keeps an aircraft within a specified airspace while awaiting further clearance.
Hold-over time (HoT)	The estimated time the anti-icing fluid will prevent the formation of ice and frost and the accumulation of snow on the protected (treated) surfaces of an aeroplane
Home base	The location, assigned by the operator to the crew member, from where the crew member normally starts and ends a duty period or a series of duty periods and where, under normal circumstances, the operator is not responsible for the accommodation of the crew member concerned
Hostile environment	(a) an environment in which: <ol style="list-style-type: none">1. a safe forced landing cannot be accomplished because the surface is inadequate;2. the helicopter occupants cannot be adequately protected from the elements;3. search and rescue response/capability is not provided consistent with anticipated exposure; or4. there is an unacceptable risk of endangering persons or property on the ground; (b) in any case, the following areas: <ol style="list-style-type: none">1. for overwater operations, the open sea areas north of 45N and south of 45S designated by the authority of the State concerned;2. those parts of a congested area without adequate safe forced landing areas.
Hot spot	A location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.
Human Factors principles	Principles which apply to aeronautical design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration to human

	performance.
Human performance	Human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.
Humidity	<ol style="list-style-type: none">1. Water vapor content of the air.2. Some measure of the water-content of air.
Hypsometric tints	A succession of shades or colour gradations used to depict ranges of elevation.
Icing	In general, any deposit or coating of ice on an object, caused by the impingement and freezing of liquid (usually super-cooled) hydrometeors. The two basic types of icing are rime and glaze
IFR	The symbol used to designate the instrument flight rules.
IFR conditions	Weather conditions below the minimum for flight under visual flight rules. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
IFR flight	A flight conducted in accordance with the instrument flight rules.
IMC	The symbol used to designate instrument meteorological conditions.
INCERFA	The code word used to designate an uncertainty phase.
Incident	Incident means an occurrence other than an accident, associated with the operation of an aircraft, which affects or could affect the safety of operations.
Infrared radiation	Electromagnetic radiation of wavelengths approximately between 0.75 and 1000 mm. See atmospheric radiation, terrestrial radiation, long wave radiation.
Initial Approach Segment	That segment of an instrument approach procedure between the initial approach fix and the intermediate approach fix or, where applicable, the final approach fixes or point.
Instrument	A device using an internal mechanism to show visually or aurally the attitude, altitude, or operation of an aircraft or aircraft part. It includes electronic devices for automatically controlling an aircraft in flight. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Instrument approach procedure	A series of predetermined manoeuvres by reference to flight instruments with specified protection from obstacles from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, to a position at which holding or en-route obstacle clearance

criteria apply.

Instrument approach procedures are classified as follows:

Non-precision approach (NPA) procedure: An instrument approach procedure which utilizes lateral guidance but does not utilize vertical guidance.

Approach procedure with vertical guidance (APV): An instrument approach procedure which utilizes lateral and vertical guidance but does not meet the requirements established for precision approach and landing operations.

Precision approach (PA) procedure: An instrument approach procedure using precision lateral and vertical guidance with minima as determined by the category of operation.

Note – Lateral and vertical guidance refers to the guidance provided either by:

- a. *a ground-based navigation aid; or*
- b. *computer-generated navigation data.*

Instrument flight time. Time during which a pilot is piloting an aircraft solely by reference to instruments and without external reference points.

Instrument ground time Time during which a pilot is practising, on the ground, simulated instrument flight in a flight simulation training device approved by CAA.

Instrument meteorological conditions (IMC) Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, less than the minima specified for visual meteorological conditions.

Note — The specified minima for visual meteorological conditions are contained in Chapter 4 of ICAO Annex 2.

Instrument time Instrument flight time or instrument ground time.

Integrated Aeronautical Information Package A package in paper, or electronic media which consists of the following elements:

- AIP, including amendment service;
- Supplements to the AIP;
- NOTAM and PIB;
- AIC; and
- checklists and lists of valid NOTAM.

Integrity (aeronautical data) A degree of assurance that an aeronautical data and its value has not been lost or altered since the data origination or authorized amendment.

Integrity (aeronautical A degree of assurance that an aeronautical data and its value has not been

data)	lost nor altered since the data origination or authorized amendment.
Integrity classification (aeronautical data)	<p>Classification based upon the potential risk resulting from the use of corrupted data. Aeronautical data are classified as:</p> <ul style="list-style-type: none">(a) routine data: there is a very low probability when using corrupted routine data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;(b) essential data: there is a low probability when using corrupted essential data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; and(c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe.
Integrity classification (aeronautical data)	<p>Classification based upon the potential risk resulting from the use of corrupted data. Aeronautical data is classified as:</p> <ul style="list-style-type: none">(a) routine data: there is a very low probability when using corrupted routine data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;(b) essential data: there is a low probability when using corrupted essential data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; and(c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe.
Intermediate Approach Segment	That segment of an instrument approach procedure between either the intermediate approach fix and the final approach fix or point, or between the end of a reversal, racetrack or dead reckoning track procedure and the final approach fix or point, as appropriate.
Intermediate holding position	A designated position intended for traffic control at which taxiing aircraft and vehicles shall stop and hold until further cleared to proceed, when so instructed by the aerodrome control tower.
International airport	Any airport designated by the Contracting State in whose territory it is situated as an airport of entry and departure for international air traffic, where the formalities incident to customs, immigration, public health, animal and plant quarantine and similar procedures are carried out.
International Airways Volcano Watch (IAVW)	<p>International arrangements for monitoring and providing warnings to aircraft of volcanic ash in the atmosphere.</p> <p><i>Note:- The IAVW is based on the cooperation of aviation and non-aviation operational units using information derived from observing sources and networks that are provided by States. The watch is coordinated by ICAO</i></p>

with the cooperation of other concerned international organizations.

International NOTAM office	An office designated by a State for the exchange of NOTAM internationally.
International NOTAM office (NOF)	An office designated by a State for the exchange of NOTAM internationally.
International operating agency	An agency of the kind contemplated in Article 77 of the Chicago Convention.
Inversion	In meteorology, a departure from usual (normal) decrease or increase with altitude of the value of an atmospheric property; also, the layer through which this departure occurs (the inversion layer). This term almost always refers to a temperature inversion.
Investigation	A process conducted for the purpose of accident and incident prevention, which includes the gathering and analysis of information, the drawing of conclusions, including the determination of causes and, when appropriate, the making of safety recommendations.
Investigator-in-charge	A person charged, on the basis of his or her qualifications, with the responsibility for the organisation, conduct and control of an investigation. This person shall be designated by CAA to direct the investigative activity of the Investigation Committee and over whose signature any required report is issued.
Isobar	A line of equal or constant pressure. It most often refers to a line drawn through all points of equal atmospheric pressure.
Isogonal	A line on a map or chart on which all points have the same magnetic variation for a specified epoch.
Isogriv	A line on a map or chart which joins points of equal angular difference between the North of the navigation grid and Magnetic North.
Isotherm	A line of equal or constant temperature.
Jet stream	Relatively strong winds concentrated within a narrow stream in the atmosphere. Generally refers to a quasi-horizontal jet stream of maximum winds embedded in the mid latitude westerly's, and concentrated in the high troposphere.
Joint rescue coordination centre (JRCC)	A rescue coordination centre responsible for both aeronautical and maritime search and rescue operations.
Landing area	That part of a movement area intended for the landing or take-off of aircraft.
Landing decision point (LDP)	The point used in determining landing performance from which, an engine failure having been recognised at this point, the landing may be safely continued or a balked landing initiated

Landing direction indicator	A device to indicate visually the direction currently designated for landing and for take-off.
Landing distance available (LDA)	The length of the runway which is declared available by the State of the aerodrome and suitable for the ground run of an aeroplane landing
Landing surface	That part of the surface of an aerodrome which the aerodrome authority has declared available for the normal ground or water run of aircraft landing in a particular direction.
Landplane	A fixed wing aircraft which is designed for taking off and landing on land and includes amphibians operated as landplanes
Lapse rate	The rate of change of any meteorological element with height.
Large Aircraft	An aircraft, classified as an aeroplane with a maximum take-off mass of more than 5700 kg, or a multi-engined helicopter. <i>(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)</i>
Level	A generic term relating to the vertical position of an aircraft in flight and meaning variously, height, altitude or flight level.
Licensing authority	The competent authority that issued the licence, or to which a person applies for the issue of a licence, or, when a person has not yet applied for the issue of a licence, the competent authority in accordance with civil aviation regulations.
Light aircraft pilot licence (LAPL)	The leisure pilot licence
Lighter-than-air aircraft	Any aircraft supported chiefly by its buoyancy in the air.
Likely	In the context of the medical provisions, likely means with a probability of occurring that is unacceptable to the medical assessor.
Limit loads	The maximum loads assumed to occur in the anticipated operating conditions.
Limitation	A condition placed on the medical certificate, licence or cabin crew medical report that shall be complied with whilst exercising the privileges of the licence, or cabin crew licence
Load factor	The ratio of a specified load to the total weight of the aircraft. The specified load is expressed in terms of any of the following: aerodynamic forces, inertia forces, or ground or water reactions. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Local day	A 24-hour period commencing at 00:00 local time

Local helicopter operation	A commercial air transport operation of helicopters with a maximum certified take-off mass (MCTOM) over 3175 kg and a maximum operational passenger seating configuration (MOPSC) of nine or less, by day, over routes navigated by reference to visual landmarks, conducted within a local and defined geographical area specified in the operations manual
Local night	A period of 8 hours falling between 22:00 and 08:00 local time
Logon address	A specified code used for data link logon to an ATS unit.
Low visibility procedures (LVP)	Procedures applied at an aerodrome for the purpose of ensuring safe operations during lower than standard category I, other than standard category II, category II and III approaches and low visibility take-offs
Low visibility take-off (LVTO)	A take-off with an RVR lower than 400 m but not less than 75 m
Lower than standard category I (LTS CAT I) operation	A category I instrument approach and landing operation using category I DH, with an RVR lower than would normally be associated with the applicable DH but not lower than 400 m
Low-level clouds	Stratus (ST), Stratocumulus (SC), and in some degree, Nimbostratus (NS) are low clouds.
LSA aircraft	means a light sport aeroplane which has all of the following characteristics: (a) a Maximum Take-off Mass (MTOM) of not more than 600 kg; (b) a maximum stalling speed in the landing configuration (VS0) of not more than 45 knots Calibrated Airspeed (CAS) at the aircraft's maximum certificated take-off mass and most critical centre of gravity; (c) a maximum seating capacity of no more than two persons, including the pilot; (d) a single, non-turbine engine fitted with a propeller; (e) a non-pressurised cabin. <i>(Source: European Commission Regulation (EU) No 1321/2014 of 26 November 2014)</i>
Magnetic variation	The angular difference between True North and Magnetic North. <i>Note:- The value given indicates whether the angular difference is East or West of True North.</i>
Maintenance	The performance of tasks required to ensure the continuing airworthiness of an aircraft, including any one or combination of overhaul, repair, inspection, replacement, modification or defect rectification of an aircraft or component, with the exception of pre-flight inspection. <i>(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)</i>
Maintenance programme	A document which describes the specific scheduled maintenance tasks and their frequency of completion and related procedures, such as a reliability

programme, necessary for the safe operation of those aircraft to which it applies.

Manoeuvring area

That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons.

Marking

A symbol or group of symbols displayed on the surface of the movement area in order to convey aeronautical information.

Master Minimum Equipment List (MMEL)

A master list (including a preamble) appropriate to an aircraft type which determines those instruments, items of equipment or functions that, while maintaining the level of safety intended in the applicable airworthiness certification specifications, may temporarily be inoperative either due to the inherent redundancy of the design, and/or due to specified operational and maintenance procedures, conditions and limitations, and in accordance with the applicable procedures for continued airworthiness.

(Source: Annex III to regulation (EC) No 1899/2006 of the European parliament and of the council of 12 December 2006)

Maximum mass

Maximum certificated take-off mass.

Maximum operational passenger seating configuration (MOPSC)

The maximum passenger seating capacity of an individual aircraft, excluding crew seats, established for operational purposes and specified in the operations manual. Taking as a baseline the maximum passenger seating configuration established during the certification process conducted for the type certificate (TC), supplemental type certificate (STC) or change to the TC or STC as relevant to the individual aircraft, the MOPSC may establish an equal or lower number of seats, depending on the operational constraints

MCAR

Maldivian Civil Aviation Regulations adopted by the CAA.

Medical Assessment

The evidence issued by a Contracting State that the licence holder meets specific requirements of medical fitness.

Medical assessor

A physician qualified and experienced in the practice of aviation medicine who evaluates medical reports submitted to CAA by medical examiners.

Medical examiner

A physician with training in aviation medicine and practical knowledge and experience of the aviation environment, who is designated by CAA to conduct medical examinations of fitness of applicants for licences or ratings for which medical requirements are prescribed.

Medical passenger

A medical person carried in a helicopter during a HEMS flight, including but not limited to doctors, nurses and paramedics

Metadata

Data about data (ISO 19115).

Note:- Data that describes and documents data.

Meteorological authority	The authority providing or arranging for the provision of meteorological service for air navigation on behalf of a Contracting State.
Meteorological bulletin	A text comprising meteorological information preceded by an appropriate heading.
Meteorological element	Any one of the properties or conditions of the atmosphere which together specify the weather at a given place for any particular time (for example, air temperature, pressure, wind, humidity, thunderstorm and fog).
Meteorological information	Meteorological report, analysis, forecast, and any other statement relating to existing or expected meteorological conditions.
Meteorological office	An office designated to provide meteorological service for international air navigation.
Meteorological report	A statement of observed meteorological conditions related to a specified time and location.
Meteorological satellite	An artificial Earth satellite making meteorological observations and transmitting these observations to Earth.
Microlight	<p>An aeroplane having no more than two seats, V_{so} not exceeding 35 knots (65 KM/h) CAS, and a maximum take-off mass of no more than:</p> <ul style="list-style-type: none">— 300 kg for a landplane, single seater; or— 450 kg for a landplane, two-seater; or— 330 kg for an amphibian or floatplane, single seater; or— 495 kg for an amphibian or floatplane, two-seater, provided that a microlight capable of operating as both a floatplane and a landplane falls below both MTOM limits, as appropriate.
	<p><i>Note: Foot-launched aircraft are excluded from this definition.</i></p> <p><i>(Source: JAR-I)</i></p>
Middle-level clouds	Alto cumulus (AC) and Altostratus (AS) are the middle-level clouds.
Minimum descent altitude (MDA) or minimum descent height (MDH)	A specified altitude or height in a non-precision approach or circling approach below which descent must not be made without the required visual reference.

Note 1 — Minimum descent altitude (MDA) is referenced to mean sea level and minimum descent height (MDH) is referenced to the aerodrome elevation or to the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. A minimum descent height for a circling approach is referenced to the aerodrome elevation.

Note 2 — The required visual reference means that section of the visual

aids or of the approach area which should have been in view for sufficient time for the pilot to have made an assessment of the aircraft position and rate of change of position, in relation to the desired flight path. In the case of a circling approach the required visual reference is the runway environment.

Note 3 — For convenience when both expressions are used they may be written in the form “minimum descent altitude/ height” and abbreviated “MDA/H”.

Minimum en-route altitude (MEA)

The altitude for an en-route segment that provides adequate reception of relevant navigation facilities and ATS communications. Complies with the airspace structure and provides the required obstacle clearance.

Minimum Equipment List (MEL)

A list (including a preamble) which provides for the operation of aircraft, under specified conditions, with particular instruments, items of equipment or functions inoperative at the commencement of flight. This list is prepared by the operator for his own particular aircraft taking account of their aircraft definition and the relevant operational and maintenance conditions in accordance with a procedure approved by CAA.

(Source: Annex III to regulation (EC) No 1899/2006 of the European parliament and of the council of 12 December 2006)

Minimum obstacle clearance altitude (MOCA)

The minimum altitude for a defined segment of flight that provides the required obstacle clearance.

Minimum sector altitude

The lowest altitude which may be used which will provide a minimum clearance of 300 m (1 000 ft) above all objects located in an area contained within a sector of a circle of 46 km (25 NM) radius centered on a radio aid to navigation.

Missed Approach Point (MAPT)

That point in an instrument approach procedure at or before which the prescribed missed approach procedure must be initiated in order to ensure that the minimum obstacle clearance is not infringed.

Missed approach procedure

The procedure to be followed if the approach cannot be continued.

Mixed precipitation (Rain and snow)

Mixed precipitation (rain and snow) Precipitation consisting of a mixture of rain and wet snow. It usually occurs when the temperature of the air layer near the ground is slightly above freezing. The British term for this mixture is sleet (which has a different meaning in the United States).

Movement area

That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the maneuvering area and the apron.

Multi-crew cooperation (MCC)

The functioning of the flight crew as a team of cooperating members led by the pilot-in-command.

Multi-pilot aircraft

for aeroplanes, it means aeroplanes certificated for operation with a

minimum crew of at least two pilots;

for helicopters, airships and powered-lift aircraft, it means the type of aircraft which is required to be operated with a co-pilot as specified in the flight manual or by the air operator certificate or equivalent document

Multi-pilot operation

for aeroplanes, it means an operation requiring at least 2 pilots using multi-crew cooperation in either multi-pilot or single-pilot aeroplanes;

for helicopters, it means an operation requiring at least 2 pilots using multi-crew cooperation on multi-pilot helicopters

Navigation specification

A set of aircraft and flight crew requirements needed to support performance-based navigation operations within a defined airspace. There are two kinds of navigation specification:

RNP specification: A navigation specification based on area navigation that includes the requirement for performance monitoring and alerting, designated by the prefix RNP, e.g. RNP 4, RNP APCH

RNAV specification: A navigation specification based on area navigation that does not include the requirement for performance monitoring and alerting, designated by the prefix RNAV, e.g. RNAV 5, RNAV 1.

Note – The performance – Based Navigation Manual (Doc 9613), Volume II contains detailed guidance on navigation specifications

Night

The hours between the end of evening civil twilight and the beginning of morning civil twilight or such other period between sunset and sunrise, as may be prescribed by the appropriate authority.

Note — Civil twilight ends in the evening when the centre of the sun's disc is 6 degrees below the horizon and begins in the morning when the centre of the sun's disc is 6 degrees below the horizon.

Night vision goggles (NVG)

A head-mounted, binocular, light intensification appliance that enhances the ability to maintain visual surface references at night

Night vision imaging system (NVIS)

The integration of all elements required to successfully and safely use NVGs while operating a helicopter. The system includes as a minimum: NVGs, NVIS lighting, helicopter components, training and continuing airworthiness.

Nimbostratus (NS)

A principal cloud type (cloud genus), grey coloured and often dark, rendered diffuse by more or less continuously falling rain, snow, sleet, etc. of the ordinary varieties and not accompanied by lightning, thunder, or hail. Precipitation in most cases reaches the ground. Low, ragged clouds frequently occur below the layer, with which they may or may not merge

Non-hostile environment

An environment in which:

- (a) a safe forced landing can be accomplished;
- (b) the helicopter occupants can be protected from the elements; and
- (c) search and rescue response/capability is provided consistent with the anticipated exposure.

In any case, those parts of a congested area with adequate safe forced landing areas shall be considered non-hostile.

Non-precision approach (NPA) operation

An instrument approach with a minimum descent height (MDH), or DH when flying a CDFA technique, not lower than 250 ft and an RVR/CMV of not less than 750 m for aeroplanes and 600 m for helicopters

NOTAM

A notice distributed by means of telecommunication containing information concerning the establishment, condition or change in any aeronautical facility, service, procedure or hazard, the timely knowledge of which is essential to personnel concerned with flight operations.

NVIS crew member

A technical crew member assigned to an NVIS flight

NVIS flight

A flight under night visual meteorological conditions (VMC) with the flight crew using NVGs in a helicopter operating under an NVIS approval

Observation (Meteorological)

The evaluation of one or more meteorological elements.

Obstacle

All fixed (whether temporary or permanent) and mobile objects, or parts thereof, that:

- (a) are located on an area intended for the surface movement of aircraft; or
- (b) extend above a defined surface intended to protect aircraft in flight; or
- (c) stand outside those defined surfaces and that have been assessed as being a hazard to air navigation.

Note:- The term obstacle is used in MCAR 4 is solely for the purpose of specifying the charting of objects that are considered a potential hazard to the safe passage of aircraft in the type of operation for which the individual chart series is designed.

Obstacle clearance altitude (OCA) or obstacle clearance height (OCH)

The lowest altitude or the lowest height above the elevation of the relevant runway threshold or the aerodrome elevation as applicable, used in establishing compliance with appropriate obstacle clearance criteria.

Note 1 — Obstacle clearance altitude is referenced to mean sea level and obstacle clearance height is referenced to the threshold elevation or in the case of non-precision approaches to the aerodrome elevation or the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. An obstacle clearance height for a circling approach is referenced to the aerodrome elevation.

Note 2 — For convenience when both expressions are used they may be written in the form “obstacle clearance altitude/ height” and abbreviated “OCA/H”.

Obstacle Free Zone (OFZ)	The airspace above the inner approach surface, inner transitional surfaces, and balked landing surface and that portion of the strip bounded by these surfaces, which is not penetrated by any fixed obstacle other than a low-mass and frangibly mounted one required for air navigation purposes.
Obstacle/terrain data collection surface	A defined surface intended for the purpose of collecting obstacle/terrain data.
Offshore operations	Operations which routinely have a substantial proportion of the flight conducted over sea areas to or from offshore locations
Operating crew member	A crew member carrying out his/her duties in an aircraft during a flight
Operating site	A site, other than an aerodrome, selected by the operator or pilot-in-command or commander for landing, take-off and/or external load operations
Operation in performance class 1	An operation that, in the event of failure of the critical engine, the helicopter is able to land within the rejected take-off distance available or safely continue the flight to an appropriate landing area, depending on when the failure occurs
Operation in performance class 2	An operation that, in the event of failure of the critical engine, performance is available to enable the helicopter to safely continue the flight, except when the failure occurs early during the take-off manoeuvre or late in the landing manoeuvre, in which cases a forced landing may be required
Operation in performance class 3	An operation that, in the event of an engine failure at any time during the flight, a forced landing may be required in a multi-engined helicopter and will be required in a single-engined helicopter
Operational control	The responsibility for the initiation, continuation, termination or diversion of a flight in the interest of safety
Operational flight plan	The operator’s plan for the safe conduct of the flight based on considerations of aeroplane performance, other operating limitations and relevant expected conditions on the route to be followed and at the aerodromes concerned.
Operational planning	The planning of flight operations by an operator.
Operations manual	A manual containing procedures, instructions and guidance for use by operational personnel in the execution of their duties.
Operator	A person, organization or enterprise engaged in or offering to engage in an

aircraft operation.

Ornithopter

A heavier-than-air aircraft supported in flight chiefly by the reactions of the air on planes to which a flapping motion is imparted.

Orthometric height

Height of a point related to the geoid, generally presented as an MSL elevation.

Other than standard category II (OTS CAT II) operation.

A precision instrument approach and landing operation using ILS or MLS where some or all of the elements of the precision approach category II light system are not available, and with:

- (a) DH below 200 ft but not lower than 100 ft; and
- (b) RVR of not less than 350 m.

Other training device (OTD)

An aid used for pilot training other than an FSTD that provides for training where a complete flight deck or cockpit environment is not necessary

Part-FCL licence

A flight crew licence which complies with the requirements of MCAR-Aircrew

Parts and Appliances

Any instrument, equipment, mechanism, part, apparatus, appurtenance or accessory, including communications equipment, that is used or intended to be used in operating or controlling an aircraft in flight and is installed in or attached to the aircraft. It includes parts of an airframe, engine or propeller.

(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008)

Passenger classification

Passenger classification, for the purpose of:

- (a) 'adult' means a person of an age of 12 years and above;
- (b) 'child/children' means persons who are of an age of two years and above but who are less than 12 years of age;
- (c) 'infant' means a person under the age of two years

Past weather

Predominant characteristic of the weather which had existed at an observing station during a given period of time (during the preceding hour or six hours), specified in the international SYNOP code.

Performance class A aeroplanes

Multi-engined aeroplanes powered by turbo-propeller engines with a maximum operational passenger seating configuration (MOPSC) of more than nine or a maximum take-off mass exceeding 5 700 kg, and all multi-engined turbo-jet powered aeroplanes

Performance class B aeroplanes

Aeroplanes powered by propeller engines with an MOPSC of nine or less and a maximum take-off mass of 5 700 kg or less

Performance class C aeroplanes

Aeroplanes powered by reciprocating engines with an MOPSC of more than nine or a maximum take-off mass exceeding 5 700 kg

Performance criteria	Simple, evaluative statements on the required outcome of the competency element and a description of the criteria used to judge whether the required level of performance has been achieved. Pilot (to). To manipulate the flight controls of an aircraft during flight time.
Pilot flying (PF)	The pilot, who for the time being, is in charge of the controls of an aircraft. <i>(Source: JAR-I)</i>
Pilot not flying (PNF)	The pilot who is assisting the Pilot flying in accordance with the multi-crew co-operation concept, when the required flight crew is more than one. <i>(Source: JAR-I)</i>
Pilot-in-command	The pilot [who is] responsible for the operation and safety of an aircraft during flight time. <i>(Source: JAR-I)</i>
Pilot-in-command under supervision (PICUS)	A co-pilot performing, under the supervision of the pilot-in-command, the duties and functions of a pilot-in-command
Point light	A luminous signal appearing without perceptible length.
Portrayal	Presentation of information to humans (ISO 19117).
Position (Geographical)	Set of coordinates (latitude and longitude) referenced to the mathematical reference ellipsoid which define the position of a point on the surface of the Earth.
Positioning	The transferring of a non-operating crew member from one place to another, at the behest of the operator, excluding the time from home to the designated reporting place at home base and vice versa, as well as the time for local transfer from a place of rest to the commencement of duty and vice versa
Post spacing	Angular or linear distance between two adjacent elevation points.
Powered sailplane	An aircraft equipped with one or more engines having, with engines inoperative, the characteristics of a sailplane
Powered-lift	A heavier-than-air aircraft capable of vertical take-off, vertical landing, and low-speed flight, which depends principally on engine-driven lift devices or engine thrust for the lift during these flight regimes and on non-rotating aerofoil(s) for lift during horizontal flight.
Powered-lift aircraft	Any aircraft deriving vertical lift and in flight propulsion/lift from variable geometry rotors or engines/propulsive devices attached to or contained within the fuselage or wings.
Power-unit	A system of one or more engines and ancillary parts which are together necessary to provide thrust, independently of the continued operation of

any other powerunit(s), but not including short period thrust-producing devices.

Precipitation

Any of all of the forms of water particles, whether liquid or solid, that fall from the atmosphere and reach the ground. The forms of precipitation are: rain, drizzle, snow, snow grains, snow pellets, diamond dust, hail, and ice pellets. See also acid precipitation.

Precision

The smallest difference that can be reliably distinguished by a measurement process.

Note.— In reference to geodetic surveys, precision is a degree of refinement in performance of an operation or a degree of perfection in the instruments and methods used when taking measurements.

Precision approach procedure

An instrument approach procedure utilizing azimuth and glide path information provided by ILS or PAR.

Pre-flight information bulletin (PIB)

A presentation of current NOTAM information of operational significance, prepared prior to flight.

Pre-flight Inspection

The inspection carried out before flight to ensure that the aircraft is fit for the intended flight.

(Source: Commission regulation (EC) No 2042/2003 of 20 November 2003)

Preliminary Report

The communication used for the prompt dissemination of data obtained during the early stages of the investigation.

Present weather

Weather at a station at the time of observation.

Pressure

A type of stress characterized by uniformity in all directions. In dynamics, it is that part of the stress tensor that is independent of viscosity and depends only upon the molecular motion appropriate to the local temperature and density. It is the negative of the mean of the three normal stresses, and is, therefore, a scalar quantity expressed in units of force per unit area. In meteorology, commonly used for atmospheric pressure.

Pressure-altitude

An atmospheric pressure expressed in terms of altitude which corresponds to that pressure in the Standard Atmosphere.

Pressure-altitude

An atmospheric pressure expressed in terms of altitude which corresponds to that pressure in the Standard Atmosphere.

Prevailing visibility

The greatest visibility value, observed in accordance with the definition of “visibility”, which is reached within at least half the horizon circle or within at least half of the surface of the aerodrome. These areas could comprise contiguous or non-contiguous sectors.

Note:- This value may be assessed by human observation and/or instrumented systems. When instruments are installed, they are used to

obtain the best estimate of the prevailing visibility.

Principal place of business	The head office or registered office of the organisation within which the principal financial functions and operational control of the activities referred to in this Regulation are exercised
Printed communications	Communications which automatically provide a permanent printed record at each terminal of a circuit of all messages which pass over such circuit.
Prioritisation of ramp inspections	The dedication of an appropriate portion of the total number of ramp inspections conducted by or on behalf of a competent authority on an annual basis as provided in Part-ARO
Private pilot	A pilot who holds a licence which prohibits the piloting of aircraft in operations for which remuneration is given, with the exclusion of instruction or examination activities, as established in Part-FCL
Problematic use of substances	<p>The use of one or more psychoactive substances by aviation personnel in a way that:</p> <ul style="list-style-type: none">(a) constitutes a direct hazard to the user or endangers the lives, health or welfare of others; and/or(b) causes or worsens an occupational, social, mental or physical problem or disorder.
Procedure altitude/height	A specified altitude/height flown operationally at or above the minimum altitude/height and established to accommodate a stabilized descent at a prescribed descent gradient/angle in the intermediate/final approach segment.
Procedure turn	<p>A manoeuvre in which a turn is made away from a designated track followed by a turn in the opposite direction to permit the aircraft to intercept and proceed along the reciprocal of the designated track.</p> <p><i>Note 1:- Procedure turns are designated “left” or “right” according to the direction of the initial turn.</i></p> <p><i>Note 2:- Procedure turns may be designated as being made either in level flight or while descending, according to the circumstances of each individual procedure.</i></p>
Product	<p>An aircraft, engine or propeller.</p> <p><i>(Source: Regulation (EC) No 216/2008 of the European parliament and of the council of 20 February 2008</i></p>
Proficiency check	The demonstration of skill to revalidate or renew ratings, and including such oral examination as may be required
Prognostic chart	A forecast of a specified meteorological element(s) for a specified time or period and a specified surface or portion of airspace, depicted graphically on a chart.

Prohibited area	An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is prohibited.
Propeller	A complete propeller including all parts attached to and rotating with the hub and blades, and all equipment required for the control and operation of the propeller. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Protective breathing equipment	Breathing equipment for protection against smoke, fumes and other harmful gases. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Psychoactive substances	Alcohol, opioids, cannabinoids, sedatives and hypnotics, cocaine, other psychostimulants, hallucinogens, and volatile solvents, whereas coffee and tobacco are excluded.
Public interest site (PIS)	A site used exclusively for operations in the public interest
Qualification test guide (QTG)	A document designed to demonstrate that the performance and handling qualities of an FSTD represent those of the aircraft, class of aeroplane or type of helicopter, simulated within prescribed limits and that all applicable requirements have been met. The QTG includes both the data of the aircraft, class of aeroplane or type of helicopter and FSTD data used to support the validation
Quality	Degree to which a set of inherent characteristics fulfils requirements (ISO 9000*). <i>Note 1.— The term “quality” can be used with adjectives such as poor, good or excellent.</i> <i>Note 2.— “Inherent”, as opposed to “assigned”, means existing in something, especially as a permanent characteristic.</i>
Quality assurance	Part of quality management focused on providing confidence that quality requirements will be fulfilled (ISO 9000).
Quality control	Part of quality management focused on fulfilling quality requirements (ISO 9000).
Quality management	Coordinated activities to direct and control an organization with regard to quality (ISO 9000).
Quality system	Documented organizational procedures and policies; internal audit of those policies and procedures; management review and recommendation for quality improvement.

Radiation	Emission or transfer of energy in the form of electromagnetic waves. The process by which electromagnetic radiation is propagated through free space by virtue of joint undulatory variations in the electric and magnetic fields in space. This concept is to be distinguished from conduction and convection.
Radio navigation service	A service providing guidance information or position data for the efficient and safe operation of aircraft supported by one or more radio navigation aids.
Radiotelephony	A form of radio communication primarily intended for the exchange of information in the form of speech.
Ramp inspection	The inspection of aircraft, of flight and cabin crew qualifications and of flight documentation in order to verify the compliance with the applicable requirements
Rated air traffic controller	An air traffic controller holding a licence and valid ratings appropriate to the privileges to be exercised.
Rating	An authorization entered on or associated with a licence and forming part thereof, stating special conditions, privileges or limitations pertaining to such licence.
RCP type	A label (e.g. RCP 240) that represents the values assigned to RCP parameters for communication transaction time, continuity, availability and integrity.
Rectification interval	A limitation on the duration of operations with inoperative equipment
Reference time	The local time at the reporting point in a time zone band 2 hours wide around the local time where a crew member is acclimatised
Refractive error	The deviation from emmetropia measured in dioptres in the most ametropic meridian, measured by standard methods
Regional Air Navigation Agreement	Agreement approved by the Council of ICAO normally on the advice of a regional air navigation meeting.
Rejected take-off distance available (RTODAH)	The length of the final approach and take-off area declared available and suitable for helicopters operated in performance class I to complete a rejected take-off;
Rejected take-off distance required (RTODRH)	The horizontal distance required from the start of the take-off to the point where the helicopter comes to a full stop following an engine failure and rejection of the take-off at the take-off decision point
Relative humidity	The (dimensionless) ratio of the actual vapor pressure of the air to the saturation vapor pressure. The relative humidity is usually expressed in per cent, and can be computed from psychrometric data. See humidity.

Relief	The inequalities in elevation of the surface of the Earth represented on aeronautical charts by contours, hypsometric tints, shading or spot elevations.
Remote pilot	A person charged by the operator with duties essential to the operation of a remotely piloted aircraft and who manipulates the flight controls, as appropriate, during flight time.
Remote pilot station	The component of the remotely piloted aircraft system containing the equipment used to pilot the remotely piloted aircraft.
Remotely piloted aircraft system (RPAS)	A remotely piloted aircraft, its associated remote pilot station(s), the required command and control links and any other components as specified in the type design.
Rendering (a licence) valid	The action taken by CAA, as an alternative to issuing its own licence, in accepting a licence issued by an ICAO Contracting State as the equivalent of its own licence.
Renewal' (of, e.g. a rating or certificate)	The administrative action taken after a rating or certificate has lapsed for the purpose of renewing the privileges of the rating or certificate for a further specified period consequent upon the fulfilment of specified requirements
Reporting point	<p>A specified geographical location in relation to which the position of an aircraft can be reported.</p> <p><i>Note;- There are three categories of reporting points: ground-based navigation aid, intersection and waypoint. In this context of this definition ,intersection is a significant point expressed as radials, bearings and /or distances from ground-based navigation aids. A reporting point can be indicated as “on request” or as “ compulsory”</i></p>
Required communication performance (RCP)	A statement of the performance requirements for operational communication in support of specific ATM functions.
Required communication performance type (RCP type)	A label (e.g. RCP 240) that represents the values assigned to RCP parameters for communication transaction time, continuity, availability and integrity.
Required navigation performance (RNP)	<p>A statement of the navigation performance necessary for operation within a defined airspace.</p> <p><i>Note — Navigation performance and requirements are defined for a particular RNP type and/or application.</i></p>
Requirement	Need or expectation that is stated, generally implied or obligatory (ISO 9000*).

Note 1.— “Generally implied” means that it is custom or common practice for the organization, its customers and other interested parties, that the need or expectation under consideration is implied.

Note 2.— A qualifier can be used to denote a specific type of requirement, e.g. product requirement, quality management requirement, customer requirement.

Note 3.— A specified requirement is one which is stated, for example, in a document.

Note 4.— Requirements can be generated by different interested parties.

Rescue	An operation to retrieve persons in distress, provide for their initial medical or other needs, and deliver them to a place of safety.
Rescue coordination centre (RCC)	A unit responsible for promoting efficient organization of search and rescue services and for coordinating the conduct of search and rescue operations within a search and rescue region.
Rescue subcentre (RSC)	A unit subordinate to a rescue coordination centre, established to complement the latter according to particular provisions of the responsible authorities.
Reserve	A period of time during which a crew is required by the operator to be available to receive an assignment for a flight, positioning or other duty with at least a 10 hour notification before the start of the assigned duty
Resolution	A number of units or digits to which a measured or calculated value is expressed and used.
Rest facility	A bunk or seat with leg and foot support that provides a crew member with a sleep opportunity on board an aircraft.
Rest period	A continuous, uninterrupted and defined period of time, subsequent to and/or prior to duty, during which a crew member is free of all duties and reserve.
Restricted area	An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is restricted in accordance with certain specified conditions.
Revalidation¹ (of, e.g. a rating or certificate)	The administrative action taken within the period of validity of a rating or certificate which allows the holder to continue to exercise the privileges of a rating or certificate for a further specified period consequent upon the fulfilment of specified requirements
Reversal procedure	A procedure designed to enable aircraft to reverse direction during the initial approach segment of an instrument approach procedure. The sequence may include procedure turns or base turns.
Ridge (of high pressure)	In meteorology, an elongated area of relatively high atmospheric pressure, almost always associated with and most clearly identified as an area of

maximum anticyclonic curvature of wind flow.

RNP type A containment value expressed as a distance in nautical miles from the intended position within which flights would be for at least 95 per cent of the total flying time.

Example — RNP 4 represents a navigation accuracy of plus or minus 7.4 km (4 NM) on a 95 per cent containment basis.

Rotation It is a duty or a series of duties, including at least one flight duty, and rest periods out of home base, starting at home base and ending when returning to home base for a rest period where the operator is no longer responsible for the accommodation of the crew member

Rotorcraft A power-driven heavier-than-air aircraft supported in flight by the reactions of the air on one or more rotors.

Route sector A flight comprising take-off, departure, cruise of not less than 15 minutes, arrival, approach and landing phases

Route stage A route or portion of a route flown without an intermediate landing.

RPA observer A trained and competent person designated by the operator who, by visual observation of the remotely piloted aircraft, assists the remote pilot in the safe conduct of the flight.

Runway A defined rectangular area on a land aerodrome prepared for the landing and take-off of aircraft.

Runway strip A defined area including the runway and stopway, if provided:

- a. intended :to reduce the risk of damage to aircraft running off a runway; and
- b. to protect aircraft flying over it during take-off or landing operations.

Runway visual range (RVR) The range over which the pilot of an aircraft on the centre line of a runway can see the runway surface markings or the lights delineating the runway or identifying its centre line.

Runway-holding position A designated position intended to protect a runway, an obstacle limitation surface, or an ILS/MLS critical/sensitive area at which taxiing aircraft and vehicles shall stop and hold, unless otherwise authorized by the aerodrome control tower.

Note – In radiotelephony phraseologies, the expression “holding point” is used to designate the runway-holding position.

Safe forced landing Unavoidable landing or ditching with a reasonable expectancy of no injuries to persons in the aircraft or on the surface.

Safety management system	A systematic approach to managing safety, including the necessary organizational structures, accountabilities, policies and procedures.
Safety programme	An integrated set of regulations and activities aimed at improving safety.
Safety Recommendation	A proposal of the accident investigation authority of the State conducting the investigation, based on information derived from the investigation, made with the intention of preventing accidents or incidents.
Safety-sensitive personnel	Persons who might endanger aviation safety if they perform their duties and functions improperly including, but not limited to, crew members, aircraft maintenance personnel and air traffic controllers.
Sailplane	A heavier-than-air aircraft which is supported in flight by the dynamic reaction of the air against its fixed lifting surfaces, the free flight of which does not depend on an engine
Satisfactory evidence	A set of documents or activities that a Contracting State accepts as sufficient to show compliance with an airworthiness requirement.
Sea surface temperature	Temperature of the water film at the sea surface
Sea-level pressure	The atmospheric pressure at mean sea level, either directly measured or, most commonly, empirically determined from the observed station pressure.
Seaplane	A fixed wing aircraft which is designed for taking off and landing on water and includes amphibians operated as seaplanes
Search	An operation normally coordinated by a rescue coordination centre or rescue subcentre using available personnel and facilities to locate persons in distress.
Search and rescue aircraft	An aircraft provided with specialized equipment suitable for the efficient conduct of search and rescue missions.
Search and rescue facility	Any mobile resource, including designated search and rescue units, used to conduct search and rescue operations.
Search and rescue region (SRR)	An area of defined dimensions, associated with a rescue coordination centre, within which search and rescue services are provided.
Search and rescue service	The performance of distress monitoring, communication, coordination and search and rescue functions, initial medical assistance or medical evacuation, through the use of public and private resources, including cooperating aircraft, vessels and other craft and installations.
Search and rescue services units	A generic term meaning, as the case may be, rescue coordination centre, rescue sub centre or alerting post.

Sector	The time between an aircraft first moving for the purpose of taking off until it comes to rest after landing on the designated parking position.
Separate runways	Runways at the same aerodrome that are separate landing surfaces. These runways may overlay or cross in such a way that if one of the runways is blocked, it will not prevent the planned type of operations on the other runway. Each runway shall have a separate approach procedure based on a separate navigation aid
Serious incident	An incident involving circumstances indicating that an accident nearly occurred. <i>Note 1: The difference between an accident and a serious incident lies only in the result.</i>
Serious Injury	any injury, which is sustained by a person in an accident and which: (a) requires hospitalization for more than 48 hours, commencing within 7 days from the date the injury was received; (b) results in a fracture of any bone (except simple fractures of fingers, toes, or nose); (c) causes severe haemorrhages, nerve muscle, or tendon damage; (d) involves any internal organ; or (e) involves second or third degree burns, or any burns affecting more than 5 per cent of the body surface.
Shoulder	An area adjacent to the edge of a pavement so prepared as to provide a transition between the pavement and the adjacent surface.
SIGMET information	Information issued by a meteorological watch office concerning the occurrence or expected occurrence of specified en-route weather phenomena which may affect the safety of aircraft operations.
Signal area	An area on an aerodrome used for the display of ground signals.
Significant	In the context of the medical provisions, significant means to a degree or of a nature that is likely to jeopardize flight safety.
Significant point	A specified geographical location used in defining an ATS route or the flight path of an aircraft and for other navigation and ATS purposes. <i>Note.— There are three categories of significant points: ground-based navigation aid, intersection and waypoint. In the context of this definition, intersection is a significant point expressed as radials, bearings and/or distances from groundbased navigation aids.</i>
Single day free of duty	A time free of all duties consisting of a single day and two local nights and which may include a rest period as part of the day off.

Single-pilot aircraft	An aircraft certificated for operation by one pilot
Skill test	The demonstration of skill for a licence or rating issue, including such oral examination as may be required
Small aircraft	An aircraft of a maximum certificated take-off mass of 5 700 kg or less.
SNOWTAM	A special series NOTAM notifying the presence or removal of hazardous conditions due to snow, ice, slush or standing water associated with snow, slush and ice on the movement area, by means of a specific format.
Solar radiation	The total electromagnetic radiation emitted by the Sun.
Solo flight time	Flight time during which a student pilot is the sole occupant of an aircraft.
Special VFR flight	A VFR flight cleared by air traffic control to operate within a control zone in meteorological conditions below VMC.
Stabilised approach (SAP)	An approach that is flown in a controlled and appropriate manner in terms of configuration, energy and control of the flight path from a pre-determined point or altitude/height down to a point 50 ft above the threshold or the point where the flare manoeuvre is initiated if higher.
Standard atmosphere	See 'Atmosphere, International Standard'. <i>(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)</i>
Standard isobaric surface	An isobaric surface used on a worldwide basis for representing and analyzing the conditions in the atmosphere.
Standby	A pre-notified and defined period of time during which a crew member is required by the operator to be available to receive an assignment for a flight, positioning or other duty without an intervening rest period, as follows: (a) airport standby means a standby performed at the airport, which may lead to an assignment of duty; (b) other standby means a standby either at home or in a suitable accommodation, which may lead to an assignment of duty.
State of Design	The State having jurisdiction over the organization responsible for the type design.
State of Manufacture	The State having jurisdiction over the organization responsible for the final assembly of the aircraft.
State of Occurrence	The State in the territory of which an accident or incident occurs.
State of Registry	The State on whose register the aircraft is entered.

Note — In the case of the registration of aircraft of an international operating agency on other than a national basis, the States constituting the agency are jointly and severally bound to assume the obligations which, under the Chicago Convention, attach to a State of Registry. See, in this regard, the Council Resolution of 14 December 1967 on Nationality and Registration of Aircraft Operated by International Operating Agencies which can be found in Policy and Guidance Material on the Economic Regulation of International Air Transport (Doc 9587).

State of the Operator	The State in which the operator's principal place of business is located or, if there is no such place of business, the operator's permanent residence.
Station declination	An alignment variation between the zero degree radial of a VOR and true north, determined at the time the VOR station is calibrated.
Station pressure	Atmospheric pressure observed at a station.
Stop-way	A defined rectangular area on the ground at the end of take-off run available prepared as a suitable area in which an aircraft can be stopped in the case of an abandoned take-off.
Stratocumulus (SC)	A principal low-level cloud type (cloud genus), predominantly stratiform, in the form of relatively low gray and/or whitish layer, sheet or patch. Its elements are often arranged in bands or rolls that lie across the wind. Light rain, snow, or sleet may fall from stratocumulus.
Stratopause	The boundary layer between the stratosphere and the mesosphere at about 50 to 55 km.
Stratosphere	The atmospheric shell above the troposphere and below the mesosphere. It is characterized at first by isothermal conditions and then a gradual temperature increase. The composition of stratospheric air is basically the same as that of the lower atmosphere, with the addition of ozone.
Stratus (ST)	A principal low-level cloud type (cloud genus) in the form of a low-altitude, light to dark gray cloud layer with a rather uniform base. Stratus clouds are generally diffuse and dull. This cloud formation has little structure and looks like fog, except that it is above the ground. Stratus does not usually produce precipitation, but when it does occur it is in the form of minute particles, such as drizzle, ice crystals, or fine snow grains.
Student pilot-in-command' (SPIC)	A student pilot acting as pilot-in-command on a flight with an instructor where the latter will only observe the student pilot and shall not influence or control the flight of the aircraft
Substantial Damage	Substantial Damage means damage or failure which adversely affects the structural strength, performance, or flight characteristics of the aircraft, and which would normally require major repair or replacement of the affected

component. For the purposes of this regulation, the following conditions are not considered “substantial damage”:

- (a) for multiengine aircraft: engine failure or damage limited to an engine if only one engine fails or is damaged,
- (b) bent fairings or cowling, dented skin, small punctured holes in the skin or fabric,
- (c) ground damage to rotor or propeller blades,
- (d) and damage to landing gear, wheels, tires, flaps, engine accessories, brakes, or wing tips.

Suitable accommodation For the purpose of standby, split duty and minimum rest, a separate room, with appropriate facilities, for each crew member located in a quiet environment, equipped with a bed, sufficient ventilation, a device for regulating temperature and light intensity, and access to food and drink

Supplemental oxygen The additional oxygen required to protect each occupant against the adverse effects of excessive cabin altitude and to maintain acceptable physiological conditions.

(Source: EASA Executive Director (ED) Decision 2003/11/RM dated 05/11/2003-CS definitions)

Surface wind Wind blowing near the Earth's surface. It is measured, by convention, at a height of 10 m above ground in an area where the distance between the anemometer and any obstruction is at least 10 times the height of the obstruction.

Synoptic – scale The scale of the high- and low-pressure systems of the lower atmosphere which typical dimensions range approximately from 1000 to 2500 kilometers (synoptic-scale circulation).

Synoptic analysis The study of the synoptic observation data plotted on synoptic charts aimed at analysis of the atmospheric disturbances (for example, fronts, cyclones, and anticyclones).

Synoptic chart A weather chart reflecting the state of the atmosphere over a large area at a given moment.

Synoptic code (International synoptic surface observation, or synop, code) A code approved by the World Meteorological Organization, by which meteorological elements observed at the Earth's surface at synoptic times are encoded in groups of five figures and transmitted internationally through the available immediate communication means.

Synoptic hour Hour (UTC) determined by international agreement at which meteorological observations are made simultaneously throughout the world. The primary synoptic hours are every six hours, commencing at 00:00 UTC.

Synoptic weather A surface weather observation, made at periodic times (usually at 3-hourly

observation	and 6-hourly intervals specified by the World Meteorological Organization), of sky cover, state of the sky, cloud height, atmospheric pressure reduced to sea level, temperature, dew point, wind speed and direction, amount of precipitation, hydrometeors and lithometeors, and special phenomena that prevail at the time of the observation or have been observed since the previous specified observation.
Take-off alternate aerodrome	An alternate aerodrome at which an aircraft can land should this become necessary shortly after take-off and if it is not possible to use the aerodrome of departure
Take-off decision point (TDP)	The point used in determining take-off performance from which, an engine failure having been recognised at this point, either a rejected take-off may be made or a take-off safely continued
Take-off distance available (TODA)	In the case of aeroplanes means the length of the take-off run available plus the length of the clearway, if provided
Take-off distance available (TODAH)	In the case of helicopters means the length of the final approach and take-off area plus, if provided, the length of helicopter clearway declared available and suitable for helicopters to complete the take-off
Take-off distance required (TODRH)	In the case of helicopters means the horizontal distance required from the start of the take-off to the point at which take-off safety speed (V_{TOSS}), a selected height and a positive climb gradient are achieved, following failure of the critical engine being recognised at the TDP, the remaining engines operating within approved operating limits
Take-off flight path	The vertical and horizontal path, with the critical engine inoperative, from a specified point in the take-off for aeroplanes to 1500 ft above the surface and for helicopters to 1000 ft above the surface
Take-off mass	The mass including everything and everyone carried at the commencement of the take-off for helicopters and take-off run for aeroplanes
Take-off run available (TORA)	The length of runway that is declared available by the State of the aerodrome and suitable for the ground run of an aeroplane taking off
Task specialist	<p>A crew member in commercial air transport HEMS, HHO or NVIS operations other than a flight or cabin crew member, assigned by the operator to duties in the aircraft or on the ground for the purpose of assisting the pilot during HEMS, HHO or NVIS operations, which may require the operation of specialised on-board equipment.</p> <p><i>(Source: European Commission Regulation (EU) No. 379/2014 dated 24 April 2014)</i></p>
Target level of safety (TLS)	A generic term representing the level of risk which is considered acceptable in particular circumstances.

Taxiing	Movement of an aircraft on the surface of an aerodrome under its own power, excluding take-off and landing.
Taxiway	<p>A defined path on a land aerodrome established for the taxiing of aircraft and intended to provide a link between one part of the aerodrome and another, including:</p> <ul style="list-style-type: none">(a) Aircraft stand taxilane: A portion of an apron designated as a taxiway and intended to provide access to aircraft stands only.(b) Apron taxiway: A portion of a taxiway system located on an apron and intended to provide a through taxi route across the apron.(c) Rapid exit taxiway: A taxiway connected to a runway at an acute angle and designed to allow landing aeroplanes to turn off at higher speeds than are achieved on other exit taxiways thereby minimizing runway occupancy times.
Technical crew member	A crew member in commercial air transport HEMS, HHO or NVIS operations other than a flight or cabin crew member, assigned by the operator to duties in the aircraft or on the ground for the purpose of assisting the pilot during HEMS, HHO or NVIS operations, which may require the operation of specialised on-board equipment
Technical instructions (TI)	The latest effective edition of the 'Technical instructions for the safe transport of dangerous goods by air', including the supplement and any addenda, approved and published by the International Civil Aviation Organisation (ICAO).
Temperature	A physical quantity characterizing the mean random motion of molecules in a physical body. In other words, it is a measure of the degree of hotness or coldness of a substance.
Terminal arrival altitude (TAA)	<p>The lowest altitude that will provide a minimum clearance of 300 m (1 000 ft) above all objects located in an arc of a circle defined by a 46 km (25 NM) radius centred on the initial approach fix (IAF), or where there is no IAF on the intermediate approach fix (IF), delimited by straight lines joining the extremity of the arc to the IF.</p> <p>The combined TAAs associated with an approach procedure shall account for an area of 360 degrees around the IF.</p>
Terminal control area	A control area normally established at the confluence of ATS routes in the vicinity of one or more major aerodromes.
Terrain	The surface of the Earth containing naturally occurring features such as mountains, hills, ridges, valleys, bodies of water, permanent ice and snow, and excluding obstacles.
Thermograph	An instrument continuously recording temperature.

Thermometer	An instrument for measuring temperature; in meteorology, generally used to measure the temperature of the air or the soil.
Threat	Events or errors that occur beyond the influence of an operational person, increase operational complexity and must be managed to maintain the margin of safety. <i>Note — See Attachment E of ICAO Annex 13 — Aircraft Accident and Incident Investigation for a description of operational personnel.</i>
Threat management	The process of detecting and responding to threats with countermeasures that reduce or eliminate the consequences of threats and mitigate the probability of errors or undesired states. <i>Note.— See Attachment C to Chapter 3 of the ICAO Procedures for Air Navigation Services — Training (PANS-TRG, Doc 9868) and Circular 314 — Threat and Error Management (TEM) in Air Traffic Control for a description of undesired states.</i>
Threshold	The beginning of that portion of the runway usable for landing.
Total estimated elapsed time	For IFR flights, the estimated time required from take-off to arrive over that designated point, defined by reference to navigation aids, from which it is intended that an instrument approach procedure will be commenced, or, if no navigation aid is associated with the destination aerodrome, to arrive over the destination aerodrome. For VFR flights, the estimated time required from take-off to arrive over the destination aerodrome.
Total vertical error (TVE)	The vertical geometric difference between the actual pressure altitude flown by an aircraft and its assigned pressure altitude (flight level).
Touchdown and lift-off area (TLOF)	A load bearing area on which a helicopter may touch down or lift off.
Touchdown Zone	The portion of a runway, beyond the threshold, where it is intended landing aeroplanes first contact the runway.
Touring Motor Glider (TMG)	A specific class of powered sailplane having an integrally mounted, non-retractable engine and a non-retractable propeller. It shall be capable of taking off and climbing under its own power according to its flight manual
Traceability	Ability to trace the history, application or location of that which is under consideration (ISO 9000*). <i>Note. When considering product, traceability can relate to:</i> <ul style="list-style-type: none">– the origin of materials and parts;– the processing history; and– the distribution and location of the product after delivery.
Track	The projection on the earth's surface of the path of an aircraft, the

direction of which path at any point is usually expressed in degrees from North (true, magnetic or grid).

Traffic avoidance advice	Advice provided by an air traffic services unit specifying manoeuvres to assist a pilot to avoid a collision.
Traffic information	Information issued by an air traffic services unit to alert a pilot to other known or observed air traffic which may be in proximity to the position or intended route of flight and to help the pilot avoid a collision.
Traffic load	The total mass of passengers, baggage, cargo and carry-on specialist equipment, including any ballast
Transfer of control point	A defined point located along the flight path of an aircraft, at which the responsibility for providing air traffic control service to the aircraft is transferred from one control unit or control position to the next.
Transferring unit	Air traffic control unit in the process of transferring the responsibility for providing air traffic control service to an aircraft to the next air traffic control unit along the route of flight.
Transition altitude	The altitude at or below which the vertical position of an aircraft is controlled by reference to altitudes.
Tropopause	The boundary layer between the troposphere and stratosphere, where an abrupt change in temperature lapse rate usually occurs. It is defined as the lowest level at which the lapse rate decreases to 2°C km-1 or less, provided that the average lapse rate between this level and all higher levels within 2 km does not exceed 2°C km-1. Occasionally, a second tropopause may be found if the lapse rate above the first tropopause exceeds 3°C km-1.
Tropical cyclone	Generic term for a non-frontal synoptic-scale cyclone originating over tropical or sub-tropical waters with organized convection and definite cyclonic surface wind circulation.
Tropical Cyclone Advisory Centre (TCAC)	A meteorological centre designated by regional air navigation agreement to provide advisory information to meteorological watch offices, world area forecast centres and international OPMET databanks regarding the position, forecast direction and speed of movement, central pressure and maximum surface wind of tropical cyclones.
Troposphere	Lower part of the atmosphere, extending from the surface up to a height varying from about 7 to 9 km at polar regions to approximately 17 km in tropics. The troposphere is characterized by decreasing temperature with height, appreciable vertical wind motion, appreciable water vapor content, and weather.
Trough	In meteorology, an elongated area of relatively low atmospheric pressure;

the opposite of a ridge.

Type of aircraft	A categorisation of aircraft requiring a type rating as determined in the operational suitability data established in accordance with Part-21, and which include all aircraft of the same basic design including all modifications thereto except those which result in a change in handling or flight characteristics
Ultimate load	The limit load multiplied by the appropriate factor of safety.
Ultra long range operations (ULR)	Long range flights having a planned flight duration greater than 16 hours or a flight duty period that exceeds 18 hours
Ultraviolet radiation	Electromagnetic radiation of shorter wavelength than visible radiation but longer than x-rays; roughly, radiation in the wavelength interval from 10 to 4000 angstroms.
Unaided NVIS flight	In the case of NVIS operations, that portion of a VFR flight performed at night when a crew member is not using NVG
Uncertainty phase	A situation wherein uncertainty exists as to the safety of an aircraft and its occupants.
Undertaking	Any natural or legal person, whether profit-making or not, or any official body whether having its own personality or not
Unmanned free balloon	A non-power-driven, unmanned, lighter-than-air aircraft in free flight. <i>Note: Unmanned free balloons are classified as heavy, medium or light in accordance with specifications contained in MCAR 2, Appendix 4.</i>
Unstable air	Air in which static instability prevails. This condition is determined by the vertical gradients of air temperature and humidity.
Upper air observation	An observation made in the free atmosphere either directly or indirectly
Upper atmosphere	The general term applied to the atmosphere above the mesopause.
Upper-air chart	A meteorological chart relating to a specified upper-air surface or layer of the atmosphere.
V_I	The maximum speed in the take-off at which the pilot must take the first action to stop the aeroplane within the accelerate-stop distance. V _I also means the minimum speed in the take-off, following a failure of the critical engine at V _{EF} , at which the pilot can continue the take-off and achieve the required height above the take-off surface within the take-off distance
Validation	Confirmation, through the provision of objective evidence, that the

requirements for a specific intended use or application have been fulfilled (ISO 9000*).

Vectoring

Provision of navigational guidance to aircraft in the form of specific headings, based on the use of an ATS surveillance system.

V_{EF}

The speed at which the critical engine is assumed to fail during take-off

Verification

Confirmation, through the provision of objective evidence, that specified requirements have been fulfilled (ISO 9000*).

Note 1. The term “verified” is used to designate the corresponding status.

Note 2. Confirmation can comprise activities such as:

- *performing alternative calculations;*
- *comparing a new design specification with a similar proven design specification;*
- *undertaking tests and demonstrations; and*
- *reviewing documents prior to issue.*

VFR

The symbol used to designate the visual flight rules.

VFR flight

A flight conducted in accordance with the visual flight rules.

Visibility

Visibility for aeronautical purposes is the greater of:

- (a) the greatest distance at which a black object of suitable dimensions, situated near the ground, can be seen and recognized when observed against a bright background;
- (b) the greatest distance at which lights in the vicinity of 1 000 candelas can be seen and identified against an unlit background.

Note 1: The two distances have different values in air of a given extinction coefficient, and the latter b) varies with the background illumination. The former a) is represented by the meteorological optical range (MOR).

Note 2: The definition applies to the observations of visibility in local routine and special reports, to the observations of prevailing and minimum visibility reported in METAR and SPECI and to the observations of ground visibility.

Visual approach

An approach when either part or all of an instrument approach procedure is not completed and the approach is executed with visual reference to the terrain

Visual approach procedure

A series of predetermined manoeuvres by visual reference, from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, a go-around procedure can be carried out.

Visual line-of-sight (VLOS) operation	An operation in which the remote pilot or RPA observer maintains direct unaided visual contact with the remotely piloted aircraft.
Visual meteorological conditions	Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, equal to or better than specified minima. <i>Note: The specified minima are contained in MCAR 2, Chapter 4.</i>
Visual meteorological conditions (VMC)	Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, equal to or better than specified minima.
VMC	The symbol used to designate visual meteorological conditions.
Voice-automatic terminal information service (Voice-ATIS)	The provision of ATIS by means of continuous and repetitive voice broadcasts.
Volcanic Ash Advisory Centre (VAAC)	A meteorological centre designated by regional air navigation agreement to provide advisory information to meteorological watch offices, area control centres, flight information centres, world area forecast centres and international OPMET databanks regarding the lateral and vertical extent and forecast movement of volcanic ash in the atmosphere following volcanic eruptions.
VOLMET	Meteorological information for aircraft in flight. <i>Data Link-VOLMET (D- VOLMET). Provision of current aerodrome routine meteorological reports (METAR) and aerodrome special meteorological reports (SPECI), aerodrome forecasts (TAF), SIGMET, special air-reports not covered by a SIGMET and, where available, AIRMET via data link.</i> <i>VOLMET Broadcast. Provision, as appropriate, of current METAR, SPECI, TAF and SIGMET by means of continuous and repetitive voice broadcasts.</i>
V_{so}	The stall speed or the minimum steady flight speed in the landing configuration.
Warm front	The forward edge of an advancing warm air mass that is displacing cooler air in its path.
Water Vapor	Water substance in vapor (gaseous) form; one of the most important of all constituents of the atmosphere.
Waypoint	A specified geographical location used to define an area navigation route or the flight path of an aircraft employing area navigation. Waypoints are identified as either: Fly-by waypoint – A waypoint which requires turn anticipation to allow tangential interception of the next segment of a route or procedure, or

Flyover waypoint – A waypoint at which a turn is initiated in order to join the next segment of a route or procedure.

19104 — Geographic information — Terminology

19108 — Geographic information — Temporal schema

Weather

The state of the atmosphere, mainly with respect to its effects upon life and human activities. As distinguished from climate, weather consists of the short-term (minutes to about 15 days) variations of the atmosphere state.

Weather-permissible aerodrome

An adequate aerodrome where, for the anticipated time of use, weather reports, or forecasts, or any combination thereof, indicate that the weather conditions will be at or above the required aerodrome operating minima, and the runway surface condition reports indicate that a safe landing will be possible.

(Source: European Commission Regulation (EU) No. 379/2014 dated 24 April 2014)

Wet lease agreement

An agreement between air carriers pursuant to which the aircraft is operated under the AOC of the lessor;

Wet runway

A runway of which the surface is covered with water, or equivalent, less than specified by the 'contaminated runway' definition or when there is sufficient moisture on the runway surface to cause it to appear reflective, but without significant areas of standing water

Window of Circadian Low (WOCL)

The period between 02:00 and 05:59 hours in the time zone to which a crew member is acclimatised

World Area Forecast Centre (WAFC)

A meteorological centre designated to prepare and issue significant weather forecasts and upper-air forecasts in digital form on a global basis direct to States by appropriate means as part of the aeronautical fixed service.

World Area Forecast System (WAFS)

A worldwide system by which world area forecast centers provide aeronautical meteorological en-route forecasts in uniform standardized formats.

MCAR-I.2 Abbreviations and Symbols

AFM	Aircraft Flight Manual
ATC	Air Traffic Control
ANSP	Air Navigation Service Provider
CAA	Maldives Civil Aviation Authority
CAD	Civil Aviation Department
CAS	Calibrated airspeed
DOA	Design Organisation Approval
EASA	European Aviation Safety Agency
ICAO	International Civil Aviation Organisation
IFR	Instrument Flight Rules
ILS	Instrument Landing System
NDB	Non-directional Beacon
TSO	Technical Standard Order
VFR	Visual Flight Rules
VHF	Very High Frequency